FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1077 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEAR			GROUF	_	VEHICLE TYPE PC=passenger car; LDT=light-duty truc MDV=medlum-duty vehicle; LVW=loade vehicle welght; ALVW=adjusted LVW)	k; CATEGO d vehici ULEV=ul	e; TLEV= transitional LE\ tra LEV; SULEV=super U	ssion V:	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ Ilquefled natural gas; LPG=liquefled petroleum gas				
200.		3FMXT05.4RF5		5	MDV: 5,751-8,500 pounds ALVW	2) Count	ed as ARB LEV I ULE	v	120K / 120K	Gasoline (Indolene)				
No.			PORATIVE LY (EVAF) No.		SPECIAL FEATURE EMISSION CONTROL SYS	S & TEMS (ECS)	* = not applicable	OC/TV	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TV WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O					
1	3FMX	MXE0160BBF			2TWC(2), 2HO2S		AFS/H	1AFS=air-fuel ratio s	iensor/heated AFS_EGR=exhauer					
2		•				*	—— Igas re	- gas recirculation AiR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charges						
3		•				*	TBI= t							
4		*				*	diagno	CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
EVAF No.		CS lo.	ENGINE SIZE (L				BJECT TO SFTP ARE UNDERLINED		VIATIONS:					
1	1		4.6		Ford Expedition 2WD/4WD									
1_		1	5.4		F	ord Expeditio	rd Expedition 2WD/4WD; Lincoln Navigator 2WD/4WD							
*		*	*		-		*							
*		*	*				*							

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET AVERAGE [g/mi]		NMOG @ RAF= 1.00 CH4 RAF = *		NMOG or NMHC NMHC										J		
CER	T	14MOG HAMING		NMHC	mg=millig	n-soak Ki	_ (g/mij=rui	nning loss 1000 miles	ORVR	g/galloi	n dispensed] ahrenheit	on-board re SFTP=supp	efueling vap	or recovery	q=qram		
		*	CERT [g/mi]	CERT [g/mi]	[g/mi] 0.195		[g/mi]		Ox [g/mi]			[mg/mi]	PM [g		Hwy NC		
C. C						CERT	STD	CERT	STI) C	ERT	STD	CERT	STD	CERT	STD	
		@ 50K	0.117	*		0.9	4.4	0.1	0.4		1	18	*	*	0.14	0.53	
		@ UL	0.157	*	0.280	1.2	6.4	0.2	0.6	,	1	27	*	*	0.24	0.80	
	@ 50°F & 4K *			*	*	*	*	*	*		*	*	*	*		* .	
	CO [g/mi] @ 20°F & 50K		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)			Ox [g/mi] osite)	CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
50			SFTP 2 = @ UL (Tier 1, TLEV)		CERT	STD	CERT	STD	CERT	STD	CE	RT ST			CERT	STD	
CERT	4.4	1.00		SFTP 1	*	*	*	*	*	*		* *	*	•	*		
STD	12.5	100	金属工程	SFTP 2	*	*	*	*	*	*	1	• •	•	*	+	<u> </u>	
@ UL		VAPOR	ATIVE FAM	IILY 1	EVAPORATIVE FAMILY 2				EVA	PORATI	IVE FA	MILY 3	Ε\	EVAPORATIVE FAMILY 4			
	3-D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORV		2-D	RL	ORVR	
CERT	1.1	1.0	0.01	*	*	*	*	*	*	*	•	•	*	+	*	*	
STD	2.0	2.5	0.05	*	*	*	*	*	*	*	-		- -		<u> </u>	 	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 674 day of March 2002.

Allen Lyons, Chief

New Vehicle/Engine Programs Branch