

## FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1123
New Passenger Cars, Light-Duty Trucks
and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

I IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

YEA	MODEL YEAR TEST GRO			Р	(PC=passenger ca MDV=medium-du	CLE TYPE ir; LDT=light-duty tru ty vehicle; LVW=load ALVW=adjusted LVV	ick; CATEGOI led vehicle:	「EMISSION STAND RY (LEV=low emi TLEV= transitional LE a LEV; SULEV=super U	ssion V:	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
2003 3FMXA05.4HJ			D	MDV: 3,751 - 5	,750 pounds ALV	w	ULEV		120K / 120K	Gasoline (Indolene)					
No.		VAPORATIVE AMILY (EVAF)			EMISSIC	PECIAL FEATUR N CONTROL SY		* = not applicable	000	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TW WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2					
1	3FMX	3FMXE0155BAF					S(2), EGR, SFI, C	IAL	S/HAFS≃air-fuel ratio s	ensor/heated AFS_EGP=avbauca					
2	3FMXE0155BAG			2							AIR MFI/SFI= multiport fuel injection/pulsed  AIR MFI/SFI= multiport fuel injection/sequential MFI  TBI= throttle hody injection TC/SC=turbo (sugar-				
3		*				*									
4		•				***	*	U	CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=paraitel (2) suffix=series						
EVAF No.		ECS ENGINE No. SIZE (L)			VEHIO MAKES &	MODELS	STANDARDS A	ICLES SUBJECT TO SFTP IDARDS ARE UNDERLINED ABBREVIATIONS:							
1		1	5.4		<u>Ford</u>	Ford F-150 Pickup 2WD/4WD Short Wheelbase; Ford F-150 Supercrew Pickup 2WD Short Wheelbase									
2		1	5.4		Ford F-150 Pickup 2WD/4WD Long Wheelbase										
*		*	*												
*	* *				*										

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NM _AVE	NMOG FLEET NMOG @ RAF AVERAGE [g/mi] CH4 RAF				NMOG or	muogen	nono-id	ninaluenvoe	PM≖Dar	TICIIIATE I	matter	₩ A F≃raacti	with a religion to the	arbon mono	7/2 M F-/44	1-0/0 -1-	
CER	CERT STD		NMOG	MOG NMHC CERT CERT	INMHU	diurnai+he mg=millig	or-soak L	ic (g/mij~rui	ning loss 000 miles	ORVR	[g/gallor	n dispensed ahrenheit	=on-board r	efueling vap piemental fe	or recovery	g=gram	
			CERT [g/mi]				[g/mi]	NC	x [g/mi]		нсно	mg/mi]	PM [		Hwy NO		
- ALSON (ALSON )	Alt - Mary and a second		19)	[3.,,,,,]	<u> </u>	CERT	STD	CERT	ST	0 0	CERT	STD	CERT	STD	CERT	STD	
	@ 50 @ U		0.053 *		0.100	0.7	4.4	0.1	0.4	.	1	9	*	*	0.04	0.8	
			0.065	*	0.143	1.2	6.4	0.1	0.6	ß 1		13	*				
	@ 50°	F & 4K	*	*	*	•	*	*	*		*	*	*	*	*	*	
@ 20		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)			NMHC+NC (compo	Ox [g/mi] osite)	CO [g/mi] (composite)			NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		HC+NOx	CO [g/mi] [SC03]		
50	K	SFTP 2	= @ UL (Tier	1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CE	RT ST			CERT	STD	
CERT	4.2	3.5	1000	SFTP 1	*	*	*	*	0.04	0.40	0.	3 10.	5 0.02	0.31	0.04	3.5	
STD	12.5	-5		SFTP 2	•	*	*	*	*	*	<del> </del> ,		*	*	*	•	
@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				E	EVAPORATIVE FAMILY 4			
	3-D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL			2-D	RL	ORVR	
CERT	1.3	1.0	0.01	*	1.3	1.0	0.01	*	•	*	*	*	*	*	1	*	
STD	2.0	2.5	0.05	•	2.5	3.0	0.05	•	•	*	*	*	*	+	+	*	

**BE IT FURTHER RESOLVED**: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_ day of May 2002.

Aller Lyons, Chief

New Vehicle/Engine Programs Branch