FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1128 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP			M	VEHICLE TYPE C=passenger car; LDT=light-duty tru DV=medium-duty vehicle; LVW=load vehicle weight; ALVW=adjusted LVW	ck; CATEGOR ed vehicle;	EMISSION STAND. Y (LEV=low emis 「LEV= transitional LEV LEV; SULEV=super Ut	sion /:	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200	2003 3FMXT05.4I			F8		MDV: 5,751-8,500 pounds ALVV		LEV		120K / 120K Gasoline (Tier 2 Unleade					
No.			PORATIVE ILY (EVAF)			SPECIAL FEATUR EMISSION CONTROL SYS		OC WI	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S						
1	3FM	AXE0155BAF			1	2TWC(2), 2HO2	S(2), EGR, SFI, OI	AF	S/HAFS=air-fuel ratio s	ensor/heated AFS_EGR=exhaust					
2	3FM)	3FMXE0155BAG			2	2TWC(2), 2HO2S(2),	EGR, SFI, SC, CA	gas Alf	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=fuil /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
3		*			3	2TWC(2), TWC, 2H	02S(2), EGR, SFI,	TB							
4		*			4		*	dia							
EVAI No.	F ECS ENGIN No. SIZE (I				VEHICLÉ MAKES & MODELS										
1	1		5.4			Lincoln Blackwood 2WD									
1		2 5.4				Ford F-150 Supercrew Pickup 2WD Harley Davidson Short Wheelbase									
1		3 5.4				Ford F-150 Pickup 2WD/4WD Short Wheelbase									
2		3 5.4				Ford F-150 Pickup 2WD/4WD Long Wheelbase									

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET NMOG @ RAF AVERAGE [g/mi] CH4 RAF = *				NMOG or	CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day												
CER	CERT STD		NMOG	NMHC	NMHC STD	diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram mg=milligram mi=mile K=1000 miles F=degrees Fahrenheit SFTP=supplemental federal test procedure											
			CERT [g/mi]	CERT [g/mi]	[g/mi]	-	CO [g/mi]		NOx [g/mi]		HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]		
		@ 50K	[g/m]			CERT	STD	CERT	T STI	D C	ERT	STD	CERT	STD	CERT	STD	
19.4	2112		0.099	*	0.195	1.2	5.0	0.2	0.6	3	1	22	*	*	0.1	1.2	
17. 64			0.132	*	0.280	1.6	7.3	0.2	0.9)	1	32	*	*	0.1	1.8	
	@ 50°		*	*	*	*	*	*	*	* *		•	*	*	•	*	
@ 20		LE		ier 1, TLEV)	NMHC+NC (compo				NMHC+NOx [g/mi] [US06]			O [g/mi] [US06]	NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
50	50K		= @ UL (Tie	r 1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CE	RT STE	CER	T STD	CERT	STD	
CERT	4.5		data a	SFTP 1	•	*	*	*	0.09	0.60	0.	11.8	3 0.12	0.44	0.1	4.0	
STD	12.5			SFTP 2	*	*	*	*	*	*	*		*	*	*	*	
@ UL	Е	VAPOR	ATIVE FAI	MILY 1	EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				E	EVAPORATIVE FAMILY 4			
	3-D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVE	₹ 3-D	2-D	RL	ORVR	
CERT	1.3	1.0	0.01	*	1.3	1.0	0.01	*	*	*	*	*	*	*	•	*	
STD	2.0	2.5	0.05	*	2.5	3.0	0.05	*	*	*	*	*	*	*		*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 2014 day of June 2002.

Allen-Lyons, Chief

Mobile Source Operations Division