

DAIMLERCHRYSLER CORPORATION

EXECUTIVE ORDER A-009-0593 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP		M	VEHICLE TYPE C=passenger car; LDT=light-duty truck; DV=medium-duty vehicle; LVW=loaded rehicle weight; ALVW=adjusted LVW)	EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV)				EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200			BCRXA0287H40			MDV: 3,751-5,750 pounds ALVW			ULEV		120K / 120K Gasoline				
No.		EVAPORATIVE FAMILY (EVAF)			No.	SPECIAL FEATURES EMISSION CONTROL SYSTE			* = not applicable	O.	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing T				
1	3CR)	RXE0101GDH			1	2HO2S(2), 2WUOC,	TWC, SFI	A	WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust						
2		*			2	*					gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI				
3		*			3	*				TE	TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series				
4					4	*									
EVAI No.	_	ECS No.	ENGIN SIZE (I			VEHICLE VEHICLE STA	IICLES SUNDARDS	JBJEC ARE	T TO SFTP	ABB	REVIATIONS:				
1 1 4.7				Dodge Durango											
*	_	*	*												
*		* * *						*							
*		* * *													

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET AVERAGE [g/mi]				RAF=0.94 RAF = *	NMOG or	Initrogen	HCHO=tor	maldehyde	PM=par	ticulate	matter	H4 hydroca RAF=reactiv	ity adiuetm	ant factor	2/2 [[0/4004	1-2/2 4-1	
<u> </u> '	CERT	THE THIRD				NMHC	mg=millig	ram mi=	. [g/mi]≃rur	nning loss 000 miles	ORVR	₹ [g/gallor	dispensed] ahrenheit	≃on-board r	efueling vap plemental fe	or recovery	g≃gram	
	*	*		CERT [g/mi]	CERT [g/mi]	[g/mi]		CO [g/mi]		NOx [g/mi]		НСНО			g/mi]	Hwy NOx [g/mi]		
3000.00	256			[G/mi]			CERT	STD	CERT	ST)	CERT	STD	CERT	STD	CERT	STD	
		7	@ 50K	0.070	*	0.100	3.4	4.4	0.3	0.4		1	9	*	*	0.3	0.5	
			@ UL	0.070	*	0.143	3.4	6.4	0.3	0.6		1	13	*	*	0.3	0.8	
		@ 50°l	F & 4K	0.158	*	0.200	1.8	4.4	0.02	0.4		0.2	18	*	*	*	*	
	CO [0 @ 20°		LEV) or 50K (Tier 1, TLEV)						g/mi] osite)	NMHC+NC [g/mi] [US0					HC+NOx		[g/mi] C03]	
L	50K		SFTP 2 = @ UL (Tier 1, TLEV)			CERT	STD	CERT	STD	CERT	ST	D CE	RT ST			CERT	STD	
CE	RT	5.6	347		SFTP 1	*	*	. •	*	*	*	-	*	*	*	*		
S	TD	12.5		Mag 4	SFTP 2		*	•	*	*	*	-		*		*	*	
ര	UL -		/APOR	ATIVE FA	MILY 1	EVAPORATIVE FAMILY 2				EVA	EVAPORATIVE FAMILY 3				EVAPORATIVE FAMILY 4			
		3-D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	. ORVI		2-D	RL	ORVR	
CE	RT	1.3	1.0	0.00	1 *	*	*	*	*	*	*	*	*	*	*	*	*	
ST	D	2.0	2.5	0.05	*	*	*	*	*	*		*	*	-	*	*		

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 124 day of July 2002.

Allen Lyons, Chief

Mobile Source Operations Division