

## DAIMLERCHRYSLER CORPORATION

EXECUTIVE ORDER A-009-0598 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for exhaust and evaporative emission control systems produced by the which certification is granted.

MODEL YEAR TEST GRO					VEHICLE TYPE C=passenger car; LDT=light-duty to the control of the	aded vehicle; /W) ULEV=ultra	EMISSION STAND Y (LEV=low emis TLEV= transitional LEV LEV; SULEV=super UI	sion	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ Ilquefled natural gas; LPG=ilquefled petroleum gas) Gasoline (Indolene)				
No EVAPORATIVE					MDV: 3,751-5,750 pounds AL\		TIER 1		120K / 120K					
1	FAMILY	(EVAF)	8	No.	SPECIAL FEATU EMISSION CONTROL S	YSTEMS (ECS)	* = not applicable	ОС	/TWC=oxidizing/3-way	cot ADSTINO				
2	OUIOCE	CRXE0174GDL			HO2S(2),	TWC, SFI, OBD (F	AFS	S/HAFS=air-fuel ratio	023=0xygen sensor/heated 02S					
3		•				*	AIR	MFI/SFI= multiport	tuel injection/pulsed					
4 EVAF	ECS	*				*			BD (5) / (D)-fall					
No.	No.				VEHICLE MAKES & MODELS	VEHICLES SUBJ	ECT TO SFTP			(2) SUMIX=Series				
- 1	1 5.9			MAKES & MODELS   STANDARDS ARE UNDERLINED   ABBREVIATIONS:  Dodge Ram 1500 Pickup										
*	*	* *		+										
*	•	• •												

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

AVE	NMOG FLEET AVERAGE [g/mi]			) RAF=* AF = *	NMOG or	CH4=meti	nane NMC	G=non-CH	l4 organic	gas N		-CH4 hydroc				
CEF	CERT STD				NMHC STD	mg=millig	ram mi	KL [g/mi]=n =mile K=	unning los •1000 mile	s OR's	VR [q/qall	I-CH4 hydroc RAF≃react on dispensed Fahrenheit	l]=on-board	refueling va	2/3 D [g/tesi	]=2/3 day
			[g/mi]	[g/mi]	[g/mi]	CERT	[g/mi] STD	_ N CER	Ox [g/mi	] TD	HCHC	[mg/mi]	PM	plemental fe g/mi]	Hwy NO	rocedure  x [g/mi]
	1.7	@ 50K	*	0.24	0.32	4.0	4.4				CERT	STD	CERT	STD	CERT	STD
		@ UL	*	0.24			+	0.7		0.7		*	*	*	0.6 0.63	1.4
	@ 50°F & 4H			0.24	0.46	4.0	6.4	0.72	2   0.	98	*	*	*			
		F & 4K	*		*		*				*	+	<del> </del> _		0.03	1.96
@ 20	[g/mi] )°F &		= @ 4K (SULI V) or 50K (Ti	er 1. TI FV\	NMHC+NO	Ox [g/mi] osite)	CO (com	[g/mi] posite)		IC+NC		CO [g/mi]	NM	HC+NOx	· co	* [g/mi]
50	K	SFIP 2	= @ UL (Tier	1, TLEV)	CERT	STD	CERT	STD	CERT			[US06]		1i] [SC03]		03]
CERT	10.3			SFTP 1	*	*	*	+	OLKI	<b>⊣</b> 3	10 0	ERT ST	D CER	T STD	CERT	STD
STD	12.5		1.3	SFTP 2				<u> </u>	*		*	*   *		*	*	*
		2 0 0	364			*	*	*		1	•	* *	*	*	<del>                                     </del>	
@ UL			TIVE FAM		EVAPORATIVE FAMILY 2				EV	POR	ATIVE E	AMILY 3	<del></del>	415551		
	3-D	2-D	RL	ORVR	3-D	2-D		ORVR	3-D	2-0				VAPORATI	VE FAMIL	.Y 4
CERT	1.1	0.7	0.001	*	*	*	*	*	- <del></del>	2-1		L ORV	R 3-D	2-D	RL	ORVR
STD	2.0	2.5	0.05		*	-	*						*	*	*	*
					<u>-</u> <u>-</u> <u>-</u> -		L					<u> </u>	*	T *	*	*

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 12th day of July 2002.

Allen Lyons, Chief

Mobile Source Operations Division