

FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1081
New Passenger Cars, Light-Duty Trucks
and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP		M	VEHICLE TYPE C=passenger car; LDT=light-duty truck; DV=medium-duty vehicle; LVW=loaded rehicle weight; ALVW=adjusted LVW)	EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV)			sion /:	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)						
200		3FMXV02.0VH1			PC	1) USEPA Bin 8 2) Counted as ARB LEV I ULEV			/	100K / 100K	Gasoline (Tier 2 Unleaded)						
No.			PORATIVE LY (EVAF)				No.	SPECIAL FEATURES EMISSION CONTROL SYSTE		•	= not applicable	OC WI	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S				
1	3FM)	MXR0080BBE			1	TWC(2), HO2S(2), EGR, SFI, OBD (F)					S/HAFS=air-fuel ratio s	ensor/heated AFS_EGR=exhaust					
2		*			2	*					gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board						
3		*			3	*											
4		*			4	1	,	diagnostic prefix 2=parallel (2) suffix=series									
EVAI No.	, -	CS No.	ENGINE SIZE (L)			VEHICLE VE MAKES & MODELS STA	HICLES SUNDARDS	JBJEC ARE U	TO SFTP	ABBF	BBREVIATIONS:						
1	1		2.0				Ford: Focus, Focus Wagon										
*	* *					*											
*		*	*														
*		* *															

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET AVERAGE [g/mi]) RAF= * AF = *	NMOG or	nitrogen	HUHUSTOR	maidenvde	PM≕nar	ticulate m	natter 3	2AE=raactiv	bon CO≃ca	nt faatar	2/2 D [-/44	7-0/0 4	
CER	CERT STD 0.053 0.062		NMOG	NMHC	NMHC STD [g/mi]	mg=millig	n-soak Ki	L (g/mij=rur	ning loss	ORVR (g/gallon	dispensed]:	on-board resupp	efueling vap	or recovery	g≃gram	
0.05			CERT [g/mi]	CERT [g/mi]			[g/mi]				HCHO [mg/mi]		PM [g		Hwy NO		
Control of the Contro			[g/iii]	[8,111]		CERT	STD	CERT	STO	D C	ERT	STD	CERT	STD	CERT	STD	
4 5	@ 50K		0.036	*	0.100	0.2	3.4	0.07	0.14	4	1	15	*	*	0.02	0.19	
		@ UL	0.045	*	0.125	0.2	4.2	0.08	0.20	0	1	18	*	*	0.04	0.27	
	@ 50°	F & 4K	*	*	*	*	*	*	*		*	*	*	*	*	*	
@ 20		LE	= @ 4K (SUL V) or 50K (T	er 1, TLEV)	NMHC+NO (comp				NMHC+NOx [g/mi] [US06				NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
50	K	SFTP 2 = @ UL (Tier 1, TLEV)		1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CEF	RT STD		^	CERT	STD	
CERT	3.6	4.82	SF	TP @ 4K	*	*	*	*	0.08	0.14	3.8	8.0	0.12	0.20	0.5	2.7	
STD	10.0		SI	FTP @ UL	0.14	0.71	*	*	*		3.9	11.1	*		0.5	3.7	
@ UL		VAPORA	ATIVE FAM	ILY 1	EVAPORATIVE FAMILY 2				EVA	PORATI	VE FA	MILY 3	Ε\	EVAPORATIVE FAMILY 4			
	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVE		2-D	RL	ORVR	
CERT	0.7	0.6	0.01	0.13	*	*	*	*	*	*	*	*	*	*	*	+	
STD	2.0	2.5	0.05	0.20	*	*	*	*	*	*	*	•	+	+	 	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 24TH day of July 2002.

Aller Lyons, Chief

Mobile Source Operations Division