FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1085 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD	IR .	TEST GROUP			VEHICLE TYPE PC=passenger car; LDT=light-duty truck MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)	CATEGOR vehicle; ULEV=ultra	TLEV= transitional LEV; LEV; SULEV=super ULE	ion EVAPORATIVE USEFUL LIFE	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200		3FMXV03.0VF3			. PC		as ARB LEV I ULEV	100K / 100K	Gasoline (Tier 2 Unleaded)				
No.		APORATIVE MILY (EVAF)		No.	SPECIAL FEATURE EMISSION CONTROL SYST		* = not applicable	OC/TWC=oxidizing/3-wa	/ay cat. ADSTWC=adsorbing TWC S/HO2S=oxygen sensor/heated O2S				
1	3FMX	MXR0115BAE			2TWC, TWC, 2HO2		AFS/HAFS=air-fuel ratio	sensor/heated AFS EGR=exhaust					
2		•				*	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI						
3		*				*	TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
4		*				*							
EVAI No.		ECS ENGINE VEHICLE VEHICL No. SIZE (L) MAKES & MODELS STANDA		EHICLES SUBJ	ECT TO SFTP	BBREVIATIONS:							
1		1 3.0			Ford Taurus, Ford Taurus Wagon, Mercury Sable, Mercury Sable Wagon								
*		*	*										
* .		* *											
		*	*				*						

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET AVERAGE [g/mi]		NMOG @ RAF= * CH4 RAF = *		NMOG or	CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram											
CER	T S	STD		NMHC	NMHC	mg=millig	ot-soak K	L [g/mi]=rur	nning loss 1000 miles	ORVR	[g/gallor	ı dispensed] ahrenheit	on-board re= SFTP=supp	efueling vap	or recovery	g=gram	
0.05	з 0.	.062	CERT [g/mi]	CERT [g/mi]	[g/mi]		CO [g/mi]		łOx [g/mi]			mg/mi]	PM [g/mi]		Hwy NOx [g/mi]		
			fāvuni	[B/III]		CERT	STD	CERT	STI	D C	ERT	STD	CERT	STD	CERT	STD	
	4.6	@ 50K	0.044	*	0.100	0.4	3.4	0.06	0.1	4	*	15	*	*	0.03	0.19	
A. P.	BOX 6850000000	@ UL	0.055	*	0.125	0.5	4.2	0.09	0.2	0	*	18	*	*	0.06	0.27	
70	@ 50°F	F & 4K	*	•		*	*	*	*		*	*	*	*	*	*	
@ 20	@ 20°F & 📳 LI			LEV, ULEV, Tier 1, TLEV)	NMHC+No (comp		CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		HC+NOx i] [SC03]		[g/mi] 203]		
50	K	SFTP 2 = @ UL (Tier 1, TLEV)		CERT	STD	CERT	STD	CERT	STD	CE	RT ST	D CERT	STD	CERT	STD		
CERT	1.5	14	S	FTP @ 4K	*	*	*	*	0.07	0.14	3.	6 8.0	0.10	0.20	1.0	2.7	
STD	10.0			SFTP @ UL	0.16	0.71	*	*	*	*	3.	8 11.	1 *	*	1.2	3.7	
@ UL		/APOR/	ATIVE FA	MILY 1	EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				E	EVAPORATIVE FAMILY 4			
	3 - D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORV	R 3-D	2-D	RL	ORVR	
CERT	1.2	1.0	0.00	4 0.05	*	*	*	*	*	*	*	•	*	*	*	*	
STD	2.0	2.5	0.05	0.20	*	*	*	*	*	*	*	-	*	*	*	•	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That NMOG and HCHO certification compliance has been conditionally demonstrated based on the amended test procedures adopted by the Board on November 15, 2001. In the event the amended procedures do not become effective, the manufacturer shall be required to submit NMOG and HCHO compliance test data within 30 days after notification by the ARB or this Executive Order may be revoked and voided *ab initio*.

BE IT FURTHER RESOLVED: That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _____ day of July 2002.

Allen Lyons, Chief

Mobile Source Operations Division