

## DAIMLERCHRYSLER CORPORATION

EXECUTIVE ORDER A-009-0575 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODI		TEST GROUP			MD	VEHICLE TYPE =passenger car; LDT=light-duty truck; V=medium-duty vehicle; LVW=loaded shicle weight; ALVW=adjusted LVW)	EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV)			EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefled natural gas; LPG=liquefled petroleum gas)				
200:			3CRXV02.7VDP			PC	TLEV			100K / 100K Flexible Fuel: Ethanol (E85) / Gasolii					
No.	FAN	APORATIVE MILY (EVAF)		N	о.	SPECIAL FEATURES EMISSION CONTROL SYSTE	& :MS (ECS)								
1	3CR	XR0130XAA			1	2H02S(2), 2TW	C, SFI, OBD (	MAF	AFS/HAFS=air-fuel ratio sensor/heated AFS EGR-exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBi= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix-series						
2		*			2		*	—  ga Διι							
3		*	*				*	ПТВ							
4		*					*	dia							
EVAF No.				VEHICLE VE MAKES & MODELS STA	HICLES SUB,	ECT TO SFTP E UNDERLINED	ABBI	ABBREVIATIONS:							
1_		1	2.7			Chrysler Sebring, Chrysler Sebring Convertible, Dodge Stratus									
*		* *													
*		*	*				*								
*		* *					· · · · · · · · · · · · · · · · · · ·	*							

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

AVE	NMOG FLEET AVERAGE [g/mi]			NMOG @ RAF=1.00 (0.98) CH4 RAF = *			NMOG CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram											
CEF	0.083 0.062		NMOG CERT [g/mi]		NMHC	NMHC		UL-SUAK R	r (8/mm)-rui	nning loss 1000 miles	UKVK	( [g/gallor	dispensed ahrenheit	=on-board r SFTP=sup	efueling vap	or recovery	g=gram	
0.08					CERT [g/mi]	STD		[g/mi]	NC	x [g/mi]		HCHO	mg/mi]	PM [g		Hwy NO		
25			0.044		[9]	[g/mi] 0.125	0.4	STD	CERT			CERT	STD	CERT	STD	CERT	STD	
	@ 50K		(0.05)		*	(0.25)	(0.7)	(3.4)	(0.2)	0.4 (0.4		1 (1)	15 (15)	*	* [	0.04	0.5	
	(	D UL	0.044		*	0.156	0.4	4.2	0.2	0.6		1	18			0.03)	(0.5)	
400	@ 50	- 1	(0,	.05)		(0.31)	(0.7)	(4.2)	(0.2)	(0.6	)	(1)	(18)			(0.03)	(0.8)	
	U 30	4K		*	*	*	*	*	*	•		*	*	*	*	*	*	
@ 20	@ 20°F & 📳 LEV) or 50K (Tier 1, TLEV)					(comp	C+NOx [g/mi] CO [g/mi] composite) (composite)						CO [g/mi] [US06]			CO [g/mi] [SC03]		
	)K	3717	2 = @	UL (Her	1, ILEV)	CERT	STD	CERT	STD	CERT	STD	CE	RT STI	CER1	STD	CERT	STD	
CERT	4.3 (3.8)	14	1		SFTP 1	*	*	•	*	(0.10)	(0.25	5) (1.	7) (10.	5) (0.13)	(0.27)	(0.4)	(3.5)	
STD	12.5 (12.5)				SFTP 2	*	*	*	*	*	*	-	•		•		•	
@ UL	EVAPORATIVE FAMILY 1					EVAPORATIVE FAMILY 2				EVA	PORAT	TIVE FA	MILY 3	EV	EVAPORATIVE FAMILY 4			
0	3-D		2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVI		2-D	RL	ORVR	
CERT	1.6 (1.2)		0.8 1.0)	0.000 (0.000)	0.11 (0.11)	*	*	*	•	*	*		•	•	*	-	*	
STD	2.0 (2.0)		2.5 2.5)	0.05 (0.05)	0.20 (0.20)	*	*	*	*	*	*	*	+	*	•	•	•	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_

day of July 2002.

Allen Eyons, Chief Mobile Source Operations Division