

DAIMLERCHRYSLER CORPORATION

EXECUTIVE ORDER A-009-0576 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

	TEST GROUP				VEHICLE TYPE PC=passenger car; LDT=light-duty tr MDV=medium-duty vehicle; LVW=loa vehicle weight; ALVW=adjusted LV	uck; CATEGOR ded vehicle;	EMISSION STAND RY (LEV-low emi TLEV- transitional LE a LEV; SULEV-super U	ssion V:	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200		3CRXV03.5VD0			PC		LEV		100K / 100K	Gasoline				
No.		APORATIVE MILY (EVAF)		No	SPECIAL FEATURES & *= not applicabl EMISSION CONTROL SYSTEMS (ECS) *= not applicabl				OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S					
1	3CR	RXR0130GBA				2TWC, SFI, OBD	HAFS	5/HAFS=air-fuel ratio s	ensor/heated AES_ECD-avbauck					
2		*		2		*	gas	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
3		•		3		*	— Iтві							
4		* 5		4		*	JUAC							
EVAI No.		ECS No.	ENGINE SIZE (L		VEHICLE MAKES & MODELS	VEHICLES SUB	HICLES SUBJECT TO SFTP		ABBREVIATIONS:					
1		1	3.5		Dodge Intrepid, Chrysler Concorde, Chrysler 300M, Chrysler Intrepid									
*							* * * * * * * * * * * * * * * * * * *							
*		*	*	*										
*	* *		* *				*							

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NM AVE	NMOG FLEET AVERAGE [g/mi] CERT STD 0.083 0.062		NMOG @ RAF=0.94 CH4 RAF = *		NMOG or								rbon CO=c				
CER			NMOG	NMHC CERT [g/mi]	NMHC STD [g/mi]	diurnal+ho mg≃milligr		ւնձուովաւտ	ning loss 000 miles	OKVK	[g/ganor	dispensed] ahrenheit	l≃on-board r	efuelina var	OF recovery	dedram	
0.08			CERT [g/mi]				g/mi]				HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]		
and Security	14.00		<u> </u>	+	 	CERT	STD	CERT	STI) 0	CERT	STD	CERT	STD	CERT	STD	
10.4		@ 50K	0.041	*	0.075	0.3	3.4	0.2	0.2	!	2	15	*	*	0.03	0.3	
		@ UL	0.056	*	0.090	0.6	4.2	0.2	0.3		2	18	*	*	0.05	0.4	
1	@ 50°	F & 4K	*	*	*	*	•	*	*		*	*	*	*	•	*	
	@ 20°F & LEV) or 50K (Tier 1, Ti			ler 1, TLEV)	NMHC+NC (compo	ox [g/mi] CO [g/r osite) (compos			NMHC+No				NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
50	K	SFTP 2	= @ UL (Tier	1, TLEV)	CERT	STD	CERT	STD	CERT	STD					CERT	STD	
CERT	2.0	7.5	医水流	SFTP 1	*	*	*	*	0.04	0.14	0.	2 8.0		0.20	0.1	2.7	
STD	10.0	35.00		SFTP 2	*	*	*	*	*	•	-	•	*	+	+		
@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				F.	EVAPORATIVE FAMILY 4			
	3 - D	2-0	RL	ORVR	3-D	2-D	RL (ORVR	3-D	2-D	RL						
CERT	8.0	0.6	0.001	0.12	•	•	*	*	*	*	+ KL	URVI	R 3-D	2-D	RL	ORVR	
STD	2.0	2.5	0.05	0.20	•	*	*	*	•	*	+ +	*	- -	-	 	<u> </u>	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of July 2002.

Allen Lyons, Chief

Mobile Source Operations Division