

TOYOTA MOTOR CORPORATION

EXECUTIVE ORDER A-014-0462 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA				- (VEHICLE TYPE PC=passenger car; LDT=light-duty truc MDV=medium-duty vehicle; LVW=loade vehicle weight; ALVW=adjusted LVW)	k; CATEGOR	EMISSION STAND Y (LEV=low emis TLEV= transitional LEV LEV; SULEV=super U	ssion V:	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200	2003 3TYXT04.7HB				MDV: 3,751 – 5,570 pounds LVW	'	ULEV		120K / 150K	Gasoline				
No.		PORA ILY (E		No.	SPECIAL FEATURE EMISSION CONTROL SYS		* = not applicable	OC	C/TWC=oxidizing/3-way	g/3-way cat. ADSTWC=adsorbing TWC . O2S/HO2S=oxygen sensor/heated O2S				
1	3TY)	(R019	0A30	1	2WU-TWC, 2TWC,		AF	S/HAFS≃air-fuel ratio s	ensor/heated AFS EGR=exhaust					
2		*				*	ga	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger						
3		•				*	ТВ							
4		*				•	CA	CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
EVAF No.		CS No.	ENGINI SIZE (L		VEHICLE MAKES & MODELS S	VEHICLES SUB.	HICLES SUBJECT TO SFTP NDARDS ARE UNDERLINED		ABBREVIATIONS:					
1	1 4.7			Toyota: Tundra (2WD and 4WD)										
*		*	*		•									
*	.	*	*		•									
*		*	*											

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	OG FL RAGE [NMOG @ RAF = 0.94 CH4 RAF = *		NMOG or	CH4=methane NMOG=non-CH4 organic gases NMHC=non-CH4 hydrocarbons CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day												
CER	RT STD		NMOG	NMHC	NMHC	diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram mg=milligram mi=mile K=1000 miles F=degrees Fahrenheit SFTP=supplemental federal test procedure												
		*	CERT [g/mi]	CERT [g/mi]	[g/mi]		CO [g/mi]		Ox [g/mi]		нсно		PM [g/mi]		Hwy NO			
-54400						CERT	STD	CERT	r st	D	CERT	STD	CERT	STD	CERT	STD		
	300	@ 50K	0.066	*	0.100	1.5	4.4	0.2	0.	4	1	9	*	*	0.2	0.8		
17		@ UL	0.087		0.143	2.0	6.4	0.4	0.	6	1	13	*	*	0.3	1.2		
	@ 50°	F & 4K	0.127	*	0.200	1.7	4.4	0.1	0.4	4	1	18	*	•	*	*		
	CO [g/mi] @ 20°F & 50K		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)					g/mi] oosite)	NMHC+NOx [g/mi] [US06]			CO [g/mi] [US06]	NMHC+NOx [g/mi] [SC03]		CO [g/mi]			
50			SFTP 2 = @ UL (Tier 1, TLEV)		CERT	STD	CERT	STD	CERT	STE	CE	RT ST			CERT	STD		
CERT	5.9	221	LKATA.	SFTP 1	*	*	*	*	0.24	0.40	0 0.	.9 10.	5 0.26	0.31	0.3	3.5		
STD	12.5	744		SFTP 2	*	*	•	*	*	•	٦,		•	-		*		
@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2 EVA					VAPORATIVE FAMILY 3				EVAPORATIVE FAMILY 4				
	3-D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVI		2-D	RL	ORVR		
CERT	0.26	0.2	5 0.01	0.04	*	*	*	*	*	*	-	*	*	*	*	*		
STD	0.90	1.1	5 0.05	0.20	*	*	*	*	•	*	-	*	+	*	*			

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of July 2002.

Allen Lyons, Chief

Mobile Source Operations Division