

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA	AR TEST GROUP			M	VEHICLE TYPE C=passenger car; LDT=light-duty tr DV=medium-duty vehicle; LVW=loavehicle weight; ALVW=adjusted LVV DV: 5,751 – 8,500 pounds ALV	uck; CATEGOR' ded vehicle; T N) ULEV=ultra	LEV= transitional LEV; LEV; SULEV=super ULI	EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefled natural gas; LPG=liquefled petroleum gas) Gasoline (Tier 2 Unleaded)					
No.	FAM	PORA IILY (E XR023	VAF)	No.	SPECIAL FEATUR EMISSION CONTROL SY 2TWC(2), 2HO2S(2),	RES & STEMS (ECS)	* = not applicable	plicable OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing						
2 3		•					gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MF/SFI≔ multiport fuel injection/sequential MFi "TBI= throttle body injection TC/SC=turbo /super charger CAC=targe air cooler OBD (F) / (P)=full /partial on-board							
4		•		4			diagnostic prefix 2=parallel (2) suffix=series							
EVAI No.		CS No.	ENGINE SIZE (L)		VEHICLE MAKES & MODELS	VEHICLES SUBJ STANDARDS AR		ABBREVIATIONS:						
1	1		4.5		PORSCHE CAYENNE TURBO									
*		*	*		•									
*		* *			•									
*		* *												

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET NMOG @ RAF = * AVERAGE [g/mi] CH4 RAF = *			NMOG or	of nitroger	1 HCHO=	formaldehy	de PM=p	articulate	e matter	RAF=reac	tivity adius	O=carbon n tment factor	2/3 D [a/te	stl=2/3 day			
CER			NMOG	NMHC	NMHC	mg=millig	it-soak Ki 'am mi=	∟ig/mij=rui :mile K=:	nning loss 1000 miles	OKVK ((g/gallon egrees F	aispensea) ahrenheit	on-board i SFTP=suc	refueling vap	or recovery derail test o	tocedure g≖gram	
÷			CERT	CERT [g/mi]	[g/mi]	CO	CO [g/mi]		NOx [g/mi]		HCHO [mg/			g/mi]	Hwy NOx [g/mi]		
			[g/mi]			CERT	STD	CER1	STD) C	ERT	STD	CERT	STD	CERT	STD	
		@ 50K	0.048		0.160	0.7	4.4	0.1	0.4		0.2	18	•	•	0.003	0.53	
		@ UL	0.051	*	0.230	0.8	6.4	0.1	0.6		0.5	27	*	•	0.003	0.80	
8	@ 50	°F & 4K	. *	*	*	*	•	*	*		•	•	*	*	*	*	
CO [g/mi] @ 20°F &		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)			NMHC+NOx [g/mi] CO [g/m (composite) (compos				NMHC+NOx [g/mi] [US06]			O [g/mi] [US06]		HC+NOx ni] [SC03]		[g/mi] C03]	
50	K	SFTP 2	= @ UL (Tier	1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CE	RT ST	CER	T STD	CERT	STD	
CERT	5.0			SFTP 1		*	*	*	0.3	0.6	10	9 11.1	0.02	0.44	0.4	4.0	
STD	12.5		endaktin 43	SFTP 2	0.11	0.38	4.09	7.02	•	*		•	*	*	•	•	
@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2 EVAPOR					PORATI	RATIVE FAMILY 3 EV.				APORATIVE FAMILY 4		
	3-D	2-0) RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVI	₹ 3-D	2-D	RL	ORVR	
CERT	1.3	. 1.1	0.01	0.01	•	•	*	*	•	*		•	*	•	•	•	
STD	2.0	2.5	0.05	0.20	•	*	•	•	•	• .			•	-	•	•	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 16 day of March 2003

Allen Lyons, Chief

Mobile Source Operations Division