

TOYOTA MOTOR CORPORATION

EXECUTIVE ORDER A-014-0442-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP			VEHICLE TYPE (PC=passenger car; LDT=light-du MDV=medium-duty vehicle; LVW vehicle weight; ALVW=adjuster	EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV)			EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200		3TYXV01.8DDC			PC	TLEV			100K / 100K	Gasoline				
No.		VAPORATIVE AMILY (EVAF)		No. SPECIAL FEATURES EMISSION CONTROL SYSTE				* = not applicable	OC	/TWC=oxidizing/3-way	cat. ADSTWC=adsorbing TWC			
1	3TYXF	R011	5AK1	1			SFI, OBD (P)	MAF	S/MAPS=air-fuel ratio s	O2S=oxygen sensor/heated O2S ensor/heated AFS EGR=exhaust				
2		*			*					gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI				
3		*				*		ТВ	TBI= throttle body injection TC/SC=turbo /super charger					
4						*		CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
EVAF No.				VEHICLE MAKES & MODELS	VEH	HICLES SUBJECT TO SFTP NDARDS ARE UNDERLINED ABBREVIATIONS:								
1	1	1 1.8			Toyota: Corolla Matrix, Celica									
	*	•	*											
*		•	*					*						
*								*						

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]				RAF = 0.98 RAF = *	NMOG or	Tot thirtoge	11 110110-	ioimaluem	vue rivi≃i	oarticulati	e matter	KAHEresc	tivity adine	O=carbon n tment factor	· 2/2 D [~/4~	~41-0/2 da	
CER	0.055 0.062		NMOG			diurnal+h mg=millig	ULGUAK K	ե լց/ ռոյ–ւս	in ning los	SS UKVK	∢ [g/ga⊪c	n dispense ahrenheit	d]=on-boar	d refueling v ppiemental	apor recove	rv a≖gram	
0.05			CERT				[g/mi]		x [g/mi]	H	ICHO [r	ng/mi]	PM [g/mi]	Hwy NC		
45			19]	F9,)	 	CERT	STD	CERT	ST	CE	ERT	STD	CERT	STD	CERT	STD	
		@ 50K	0.086	*	0.125	0.9	3.4	0.3	0.4		1	15	*	*	0.2	0.5	
	104	@ UL	0.100	*	0.156	1.2	4.2	0.4	0.6		2	18	*	•	0.3	0.8	
	@ 50	0°F & 4K	*	*	*	*	*	*	*		*	•	*	*	*	*	
CO [@ 20	°F&	I L	EV) or 50K	ULEV, ULEV, (Tier 1, TLEV)	NMHC+NOx [g/mi] CO [g/mi] (composite)				NMHC+NOx [g/mi] [US06]		c	O [g/mi] [US06]		HC+NOx ni] [SC03]		[g/mi] C031	
	50K		= @ UL (TI	er 1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CEF	T STE	CER	TSTD	CERT	STD	
CERT	3.2		1.0	SFTP 1	*	*	*	*	*	*	*	*		*	*		
STD	10.0	*		SFTP 2	*	*	*	*	*	•	+	*	*	*	•	*	
@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2 EV				EVA	PORATIV	VE FAI	VILY 3	E	EVAPORATIVE FAMILY 4			
	3-D			. ORVR	3-D	2-D	RL.	ORVR	3-D	2-D	RL	ORVE		2-D	RL	ORVR	
CERT	0.4	0.8	0.0	1 0.10	*	*	*	*	*	*		*	*	•	*	*	
STD	2.0	2.9	5 0.0	5 0.20	*	*	•	*	•	*	*	+	*	+	+	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-014-0442 dated December 20, 2001.

Executed at El Monte, California on this ______ day of August 2002.

Allen Lyons, Chief

Mobile Source Operations Division