



TOYOTA MOTOR CORPORATION

EXECUTIVE ORDER A-014-0447 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP			VEHICLE TYPE (PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)			EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV)			EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefled natural gas; LPG=liquefled petroleum gas)			
			(V03.0FF	E	PC			LEV			100K / 100K	Gasoline			
No.		VAPORATIVE AMILY (EVAF)			о.	SPECIAL FEATURES EMISSION CONTROL SYSTE	& *= not applicable			OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC					
1	3TY	3TYXR0150AK1			ıŢ	2WU-TWC, TWC, 2HAFS, HO2S, SFI, OBD (P)					WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation ARI/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board dlagnostic prefix 2=parallel (2) suffix=series				
2	*			2	2										
3	*					*									
4		*			一										
EVAI No.	ECS ENGINE No. SIZE (L)				VEHICLE VEHICLES SUBJECT TO SFTP MAKES & MODELS STANDARDS ARE UNDERLINED					ABBREVIATIONS:					
1	1 3.0					Lexus RX 300 (2WD and 4WD)									
*		•													
*	* *				1			*							
*		*	*					<u>-</u>	*						

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]				RAF = 0.94 RAF = *	NMOG or	10111111094	in nunu:	•rormaiden	VOE PM#1	3amiculate	e matter	RAFSTON	thrite adies	O=carbon n	. 212 D.I		
CER	CERT STD		NMOG CERT	NMHC	NMHC STD [g/mi]	diurnal+h mg≖miliig	Ot-SORK I	ւ- [8/ավ=ւմ	nning loss 1000 miles	ORVR	g/gallon	dispensed] ahrenheit	=on-board :	refueling var	or recovery	q=qram	
0.05	5 0	0.062 [g		CERT [g/mi]			CO [g/mi]		Ox [g/mi]	F	HCHO [mg/mi]		PM [g/mi]	Hwy NOx [g/mi]		
			[9]	[6,111]		CERT	STD	CER	T STI	C	ERT	STD	CERT	STD	CERT	STD	
		@ 50K	0.043	*	0.075	0.5	3.4	0.1	0.2	2	0.2	15	*		0.1	0.3	
		@ UL	0.050	* .	0.090	0.7	4.2	0.1	0.3	1	0.3	18	.*	*	0.2	0.4	
	@ 50°F & 4K		*	•	*	*	•		•		•	*	*	*	*	•	
@ 20		ii Li	EV) or 50K (LEV, ULEV, Tier 1, TLEV)	NMHC+No (comp					C+NOx [US06]			NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
50	50K SFTP		2 = @ UL (Tier 1, TLEV)		CERT	STD	CERT	STD	CERT	STD	CEF	RT ST			CERT	STD	
CERT	5.2			SFTP 1	•	•	•	*	*	•		*	•	•	•	•	
STD	10.0			SFTP 2	•	*	*	*		*	1	*	•	•	 • • • • • • • • • • • • • • • • • • •	•	
@ UL			ATIVE FA		EVAPORATIVE FAMILY 2 EVAPOR					PORATI	VE FA	MILY 3	E	EVAPORATIVE FAMILY 4			
	3-D	2-[RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVI	R 3-D	2-D	RL	ORVR	
CERT	0.6	0.8	0.03	0.01	•	•	•	*	•	*	•	*	*	+	+ :\-		
STD	2.0	2.5	0.05	0.20	•	•	*	*	•	*	+			+	*	 	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _____ day of August 2002.

Allen Jons, Chief

Mobile Source Operations Division