NISSAN MOTOR CO., LTD

California Environmental Protection Agency
AIR RESOURCES BOARD

EXECUTIVE ORDER A-015-0382-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD		TEST GROUP			MC	VEHICLE TYPE =passenger car; LDT=light-duty truck;)V=medium-duty vehicle; LVW=loaded ehicle weight; ALVW=adjusted LVW)	CATEGOR' vehicle; 1	EMISSION STAND Y (LEV=low emis 'LEV= transitional LEV LEV; SULEV=super U	sion /:	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200	3	3NSXV03.5C7A				PC		LEV		100K / 100K Gasoline					
No.		VAPORATIVE AMILY (EVAF)		N	o.	SPECIAL FEATURES EMISSION CONTROL SYSTE		* = not applicable	OC WI	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S					
1	3NSX	NSXR0120MAB			1	2TWC(2), 2HO2	(2), SFI, OBD	. ∐AF	AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAR=secondary air injection/pulsed AIR MFUSFi= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=fuil /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
2	3NSXR0110MAA				2	2TWC, TWC, 2HO	2S(2), SFI, OBI	ga Alf							
3	3NSXR0120PAB				3		*	TB							
4		*			4		*	dia							
EVAI No.		CS No.	ENGINE SIZE (L)								ABBREVIATIONS: *				
1		1	3.5			INFINITI G35									
2		2 3.5				NISSAN MAXIMA, INFINITI 135									
3	2 3.5					NISSAN ALTIMA									
*															

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET AVERAGE [g/mi]				RAF=0.94 RAF = *	NMOG or	CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram											
CE	CERT STD		D	NMOG	NMHC	NMHC STD [g/mi]	mg=millig	ot-soak Ri gram mi=	L (g/mij=rui :mile K=1	nning lo 1000 mil	ss OR	VR [g/gallo F=degrees	n dispensed Fahrenheit]=on-board SFTP≖sup	refueling vap	or recovery derail test pi	g=gram rocedure	
0.0	060	0 0.062		CERT	CERT			CO [g/mi]		Ox [g/mi]		HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]		
				[g/mi]	[g/mi]	[5]	CERT	STD	CERT	rs	TD	CERT	STD	CERT	STD	CERT	STD	
		@	50K	0.052	*	0.075	1.0	3.4	0.1		0.2	1	15	*		0.04	0.3	
3 2		@	UL	0.055	*	0.090	1.2	4.2	0.1		0.3	1	18	*	•	0.1	0.4	
54	@ 50°F & 4K		4K	0.130	*	0.150	1.5	3.4	0.1	- (0.2	1	30	*	*	*	*	
	CO [g/mi] @ 20°F & 50K		LE	= @ 4K (SUL EV) or 50K (1	ler 1, TLEV	NMHC+NOx [g/mi] (composite)		CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]				HC+NOx ni] [SC03]	CO [g/mi] [SC03]			
			FTP 2 :	= @ UL (Tier	1, TLEV)	CERT	STD	CERT	STD	CER'	rs	TD C	ERT ST	D CER	T STD	CERT	STD	
CER	T 4.8				SFTP 1	*	*	*	*	0.11	0	.14	0.8 8.0	0.15	0.20	0.3	2.7	
STD	10.	0			SFTP 2	*	*	*	*	•		*		•		+	•	
@ UL		EVAPORATIVE FAMILY 1					EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				EVAPORATIVE FAMILY 4			
<u> </u>	3-	-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-	D R	L ORV	R 3-D	2-D	RL	ORVR	
CER	Γ 0.	.4	0.8	0.001	0.04	0.8	0.8	0.001	0.02	0.7	1.	1 0.0	0.03	3 *	*	•	*	
STD	2.	.0	2.5	0.05	0.20	2.0	2.5	0.05	0.20	2.0	2.	5 0.0	05 0.20	*	*	*		

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order. This Executive Order hereby supersedes Executive Order A-015-0382 dated February 26, 2002.

Executed at El Monte, California on this _Z___ day of May 2002.

Allen Lyons, Chief

New Vehicle / Engine Programs Branch