



MAZDA MOTOR CORPORATION

EXECUTIVE ORDER A-016-0269 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP		Р	MD۱	VEHICLE TYPE *passenger car; LDT=light-duty truck; /=medium-duty vehicle; LVW=loaded hicle weight; ALVW=adjusted LVW)	EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV)			EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefled natural gas; LPG=liquefled petroleum gas)				
			V01.8CJ	Α		PC	LEV			100K / 100K Gasoline					
No.		/APORATIVE MILY (EVAF)				SPECIAL FEATURES EMISSION CONTROL SYSTEM		* = not applicable	00	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWU=warm-up cat. O2S/HO2S=oxygen sensor/heated					
1	ЗТКХ	KXR0120PMA				TWC, HO2S(2), E0		MAF	-5/HAFS=air-tuel ratio s	ensor/heated AFS_EGR≃exhauet					
2		*				*		∥ga	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
3		*				*	#1-1-1 =	ТВ							
4		*				*									
EVAI No.		ECS ENGINE VEHICLE VEHICLES SUBJECT No. SIZE (L) MAKES & MODELS STANDARDS ARE				ABBREVIATIONS:									
1_	1 1.8					Mazda: MX-5 Miata									
		*	*			•									
*		*		T	*										
*		* *													

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]			NMOG @ RAF=0.94 CH4 RAF = *		NMOG or	CH4=methane NMOG=non-CH4 organic gases NMHC=non-CH4 hydrocarbons CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diurnal+hot-soak RL [g/mi]=running loss ORNR [g/gallon dispensed]=on-board refueling vapor recovery g=gram											
CER	T STD		NMOG	NMHC	NMHC STD	dlurnal+ho mg=milligr	COURT NE	. լցուոյ–ոսո	nning loss 1000 miles	OKVK	[g/gallor	aispensed]:	=on-board r	efueling vap piemental fe	or recovery	g≕gram	
0.05	1 1	0.062	CERT [g/mi]		[g/mi]	CO [g/mi]		NO	c [g/mi]		нсно [mg/mi]	PM (g	g/mi]		x [g/mi]	
neutrino e del con-			[3]	[9,111]		CERT	STD	CERT	STE)c	ERT	STD	CERT	STD	CERT	STD	
4.		@ 50K	0.049	*	0.075	0.6	3.4	0.1	0.2		0.4	15	*		0.1	0.3	
		@ UL	0.052	*	0.090	0.7	4.2	0.1	0.3		0.4	18	*	*	0.1	0.4	
100	@ 50	F & 4K	*	*	*	•	*	*	*		*	*	•	*	*	*	
@ 20	CO [g/mi] @ 20°F & 50K		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV) SFTP 2 = @ UL (Tier 1, TLEV)		NMHC+NOx [g/mi] CO [g (composite) (compo				NMHC+NOx [g/mi] [US06]		7	CO [g/mi] [U\$06]		HC+NOx		[g/mi] C031	
50					CERT	STD	CERT	STD	CERT	STD	CE				CERT	STD	
CERT	5.2			SFTP 1	*	*	*	*	*	*			+	*		•	
STD	10.0			SFTP 2	*	*	*	*	*	*	 		*		*	+	
@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				E'	EVAPORATIVE FAMILY 4			
	3-D	2-[ORVR	3-D	2-D	RL (ORVR	3-D	2-D	RL	ORVR		2-D	RL	ORVR	
CERT	0.9	9.0	0.005	0.03	*	*	*	•	*	*		-	*	*	*	*	
STD	2.0	2.5	0.05	0.20	*	*	*	*	*	*	•	*	+	*	+	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 26TH day of June 2002.

Allen Lyons, Chief

Mobile Source Operations Division