

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA				JP	M	VEHICLE TYPE C=passenger car; LDT=light-duty truck; DV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)	STAND (LEV=low e transitional	UST EMISSION ARD CATEGORY mission vehicle; TLEV= LEV; ULEV=ultra LEV; EV=super ULEV)	EXHAUST (EXH) / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefled natural gas; LPG=liquefled petroleum gas)					
200	2003 3HNX\			ВР		PC		LEV II LEV	120K: EXH/ORVR 150K: EVAF	Gasoline					
No.		APORA		Second	No.	SPECIAL FEATURES EMISSION CONTROL SYSTEM		OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S							
1	3HN:	3HNXR0140BBA			1	2HO2S, 2WUTWC, TWC, S	SFI, EGR, 2AF	AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed							
2		*			2	*		AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo/super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board							
3		*		2000	3	•									
4		*			4	•			diagnostic prefix 2=parall	el (2) suffix=series					
EVAI No.				ABBREVIATIONS:											
1	1 3.0			_		Honda Accord (LX/EX Sedan, LX/EX Coupe)									
		*	*												
*	*		*	•											
*	*		*			•									

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]			NMOG @ CH4 F	RAF=0.94 RAF = *	NMOG or	nitrogen	HCHQ=fort	naldehyde	PM=par	ticulate	matter	RAF=reactive	vity adjustm j≃on-board i	arbon mono ent factor refueling vap	2/3 D [g/test or recovery	]=2/3 day g=gram
CER	RT STD		NMOG CERT	NMHC CERT	STD	mg=millig:	ram mi=r	nile K=1	000 miles	F≖d	iegrees F	ahrenheit [mg/mi]	SFTP=sup	plementai fe g/mi]	deral test pu Hwy NO	ocedure
0.04	s   0	0.062	[g/mi]	[g/mi]	[g/mi]	CERT	[g/mi] STD	CERT	x [g/mi]		CERT	STD	CERT	STD	CERT	DTS
92.532	Sec. 7	@ 50K	0.025	*	0.075	0.2	3.4	0.04	0.0	5	0.3	15	*	*	0.03	0.07
		@ UL	0.028	*	0.090	0.2	4.2	0.05	0.0	7	0.4	18	*	*	0.04	0.09
	<i>ര</i> 50°	F & 4K	*	*		*	*	*	*		*	*	*	*	*	*
	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV) SFTP 2 = @ UL (Tier 1, TLEV)			NMHC+NOx [g/mi] CO [g/m (composite) (compos					CO [g/mi] [US06]		IHC+NOx ni] [SC03]		[g/mi] C03]	
@ 20 50						STD	CERT	STD	CERT	ST		RT ST			CERT	STD
CERT	1.4		details	SFTP 1	*	*	*	*	0.04	0.14	4 0.	04 8.	0.07	7 0.20	0.1	2.7
STD	10.0			SFTP 2	*	*	*	*		*		* *	*	*	*	*
	E	VAPOR	ATIVE FA	MILY 1	EVAPORATIVE FAMILY 2 EVAPO				PORA	RATIVE FAMILY 3			EVAPORATIVE FAMILY 4			
@ UL }	3-D	2-1		ORVR	3-D	2-D	RL	ORVR	3-D	2 <b>-</b> D	RI	L ORV		2-D	RL	ORVR
CERT	0.16	0.2	6 0.00	5 0.01	*	*	*	*	*	*	*		*	*	*	<u> </u>
STD	0.50	0.6	5 0.05	0.20	*	*	*	*	*	*	*	*	*	*		

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 30 day of August 2002.

Allen Lyons, Chief

Mobile Source Operations Division