

## **HYUNDAI MOTOR COMPANY**

EXECUTIVE ORDER A-254-0093
New Passenger Cars, Light-Duty Trucks
and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003:

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD	R	TEST GROUP		'	VEHICLE TYPE PC≖passenger car; LDT=light-duty t MDV≖medium-duty vehicle; LVW=lo vehicle weight; ALVW=adjusted L\	CATEGOR` vehicle; T ULEV=ultra l	LEV= transitional LE LEV; SULEV≃super U	ssion V:	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200		3HYXT03.5SLS		S	LDT: 3,751-5,750 pounds LV	1) USEPA Bin 9 2) Counted as ARB LEV I ULEV			100K / 100K	Gasoline (Tier 2 Unleaded)				
No.	FAM	APORATIVE MILY (EVAF)			SPECIAL FEATU EMISSION CONTROL S	JRES YSTEI	& VIS (ECS)	* = not applicable OC/TWC=oxidizing/3-way cat ADSTWC===						
1	3HY)	3HYXR0175PES			2HO2S(2), 2WUTWC, TWC, SFI, OBD (F)					WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust				
2		*				*		∰ga	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI					
3		*			*					TBI= throttle body injection TC/SC=turbo /euper charges				
4		•				*	· · · · · · · · · · · · · · · · · · ·	201.4	CAC=charge air cooler OBD (F) / (P)=fuil /partial on-board diagnostic prefix 2=parallel (2) suffix=series					
EVAF No.	ECS ENGINE No. SIZE (L)			VEHICLE MAKES & MODELS	VEH	IICLES SUBJ NDARDS ARI	ECT TO SFTP UNDERLINED	- 100	ABBREVIATIONS:					
1	1 3.5			Hyundai Santa Fe (2WD/4WD)										
* 					*									
*	* *		*					•						
*		*	*					*						

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bidual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

AVE	OG FL RAGE	EET [g/mi]	NMOG NMHC		NMOG or									arbon mond		
CER	T	STD			NMHC STD	mg=milli	OC-SUEK IT	ւ⊏ [Ֆւուու]–ւ ո	inning los: 1000 mile:	S UKV	rk įg/gailoi	n dispensed ahrenheit	=on-board i	ent factor efueling var plemental fe	Or recovery	/ a≖aram
0.09	3 (	0.093	CERT [g/mi]	,	[g/mi]		[g/mi]	No	Ox [g/mi]		НСНО	[mg/mi]	PM [	g/mi]		x [g/mi]
				[8,111]		CERT	STD	CER	T ST	D.	CERT	STD	CERT	STD	CERT	STD
		@ 50K	0.022	*	0.100	0.2	3.4	0.02	?	2	0.1	15	*	*	0.00	0.27
		@ UL	0.023	*	0.130	0.3	4.2	0.02	0.	3	0.1	18		•	0.00	0.40
	@ 50°	F & 4K	*	*	*	•		*	·		*	*		-		*
@ 20	@ 20°F &		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)					CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		HC+NOx	CO	[g/mi] C031
50			SFTP 2 = @ UL (Tier 1, TLEV)		CERT	STD	CERT	STD	CERT	ST	D CE	RT ST			CERT	STD
CERT	6.6			SFTP 1	٠	*	*	•	0.03	0.2	25 5	.2 10.	5 0.01		0.1	3.5
STD	12.5			SFTP 2	0.03	1.03	3.1	5.0	•	<del>                                     </del>	,   ,	• •	*	+	*	*
@ UL	E	VAPORA	TIVE FAM	ILY 1	EVAPORATIVE FAMILY 2 EV					EVAPORATIVE FAMILY 3				VAPORAT	VE EAMI	1 ∨ 4
	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D				2-D	RL	ORVR
CERT	0.9	1.2	0.03	0.02	•	*	•	*	*	*	<del>-   - ; -</del>	*	*	<del>  2-0</del>	ILL	URVR
STD	2.0	2.5	0.05	0.20	•	•	•	*	•		-	<del></del>	<del></del>	+	<del>                                     </del>	<del>                                     </del>

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

**BE IT FURTHER RESOLVED:** That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_28<sup>TM</sup> day of March 2003.

Raphoul Summing

Mobile Source Operations Division