LAND ROVER GROUP LTD.

EXECUTIVE ORDER A-277-0026 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

YEA	MODEL TEST GROU				VEHICLE TYPE PC=passenger car; LDT=light-du MDV=medium-duty vehicle; LVW vehicle weight; ALVW=adjusted	EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV)			EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200		3LRXT04.6001		1	MDV: 3,751-5,750 pounds A	ULEV			120K / 150K	Gasoline				
No.	FAMI	APORATIVE MILY (EVAF)		No.	SPECIAL FEA EMISSION CONTROL	& MS (ECS)	* = not applicable	oc	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorb					
1	3LRX	RXE0124001					AIR, SFI, OB	MAL	O/DAFO=air-fuel ratio s	O2S=oxygen sensor/heated O2S ensor/heated AFS EGR=exhaust				
2		•			•					- ■ gas recirculation AIR/PAIR=secondary air injection/pulses				
3		•						ТВ	AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo/super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series					
4		*				*								
EVA	EC	CS T	ENGIN	ĒΙ	VEHICLE	VEL	IICI EC CIID I	ECT TO SFTP		Green Press. Peru	ioi (2) suiix-seiles			
No.	N	No. SIZE (L)		.)	MAKES & MODELS	STAI	NDARDS AR	E UNDERLINED	ABBE	ABBREVIATIONS:				
1	1	1	4.6		Land Rover Discovery Series II									
*		•	*											
*		* *						*						
*	1	•		_										

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bidual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NM AVE	NMOG FLEET N AVERAGE [g/mi]			RAF=0.94 AF = *	NMOG or									carbon mono			
	CERT STD		NMOG	NMHC	NMHC STD	diurnal+ho mg=millig	t-sour iti	= [g/iiit]−tu	nning loss 1000 miles	UKVK	(g/galior	dispensed]	=on-board	refueling var	OF recovery	g≃gram	
		•	CERT [g/mi]	CERT [g/mi]	[g/mi]		[g/mi]	NO	Ox [g/mi]		HCHO	mg/mi]		plemental fe g/mi]	Hwy NO		
2 7 m at 10	1				 	CERT	STD	CERT	STI	D (CERT	STD	CERT	STD	CERT	STD	
4.5	4.1	@ 50K	0.037	*	0.100	0.7	4.4	0.1	0.4	٠ ˈ	0.3	9	*	*	0.01	0.8	
1 6 4		@ UL	0.040	*	0.143	0.8	6.4	0.1	0.6	3	0.3	13	*	•	0.01	1.2	
有量。	@ 50°	F & 4K	0.001	*	0.200	1.2	4.4	0.1	0.4	,	1	18		*	*	•	
CO [°F&	SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)			NMHC+NOx [g/mi] CO [g/m (composite) (compos				NMHC+NOx C					HC+NOx		CO [g/mi] [SC03]	
50	K	SFTP 2 = @ UL (Tier 1, TLEV		1, TLEV)	CERT	STD	CERT	STD	CERT	STD					CERT	STD	
CERT	4.1	100	2.3	SFTP 1	*	*	*	*	0.14	0.40) 1.	2 10.			0.6	3.5	
STD	12.5	7 J	122	SFTP 2	*	*	*	*	*		٠,			+	+	*	
@ UL			ATIVE FAM	ILY 1	EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				F	EVAPORATIVE FAMILY 4			
	3-D	2-D	RL	ORVR	3-D	2-D	RL.	ORVR	3-D	2-D	RL			2-D	RL	ORVR	
CERT	0.58	0.5	0.00	*	*	*	*	•	•		 '\-	*	*	2-0	I KL	UKVK	
STD	0.90	1.1	0.05	•	•	*	*	•	*	*	+ +	*		 	-		

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 2574

___ day of April 2002.

Aller Lyons, Chief
New Vehicle/Engine Programs Branch