

BAYTECH CORPORATION

EXECUTIVE ORDER A-330-0082 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

| - | MODI | R | TEST GROUP | | | VEHICLE TYPE C=passenger car; LDT=light-dut; DV=medium-duty vehicle; LVW= vehicle weight; ALVW=adjusted i | CATEGORY vehicle: T | EMISSION STAND. (LEV=low emis LEV= transitional LEV LEV; SULEV=super U | sion /: | EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles) | FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas) | | | | |
|---|-------------|-----|----------------|--------------------|-----|--|------------------------|---|------------------------|---|---|--|--|--|--|
| L | 200: | 3 | 3BYTT06.0213 | | | MDV: 5,751-8,500 pounds Al | | ULEV | | 120K / 120K | CNG | | | | |
| | No. | | PORA ILY (E | | No. | SPECIAL FEAT EMISSION CONTROL | | | * = not applicable | OC WI | OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbin WU= warm-up cat. O2S/HO2S=oxygen sensor/heal | | | | |
| L | 1 | 3BY | Γ Ε 000 | 0213 | 1 | IDI, 21 WC, 20023(2), EGK, OBD (P) MAPS/NAPS=air-fuel ratio sensor/heated AFS EGR | | | | | | | | | |
| L | 2 | * | | | 2 | TBI, 2TW | /C, 2HC | 2S(2), OBD (F | ga: | gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI | | | | | |
| Г | 3 | | * | | 3 | | * | <u> </u> | тв | TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series | | | | | |
| | 4 | | * | | 4 | | * | | dia | | | | | | |
| | EVAF No. | 1 | CS lo. | ENGINE SIZE (L) | | VEHICLE MAKES & MODELS | STA | NDARDS AR | ECT TO SFTP UNDERLINED | | REVIATIONS: * | | | | |
| | 1 | | 1 6.0 | | | Baytech: C2500 HD Utility 2WD, K2500 HD Utility 4WD, C3500 Utility 2WD, K3500 Utility 4WD, G3500 Flat Bed, W3500 Flat Bed, Workborse Stepvan | | | | | | | | | |
| L | 1 | | 2 6.0 | | | Baytech: C2500 HD Utility 2WD, K2500 HD Utility 4WD, C3500 Utility 2WD, K3500 Utility 4WD, G3500 Flat Bed, W3500 Flat Bed, Workhorse Stepvan | | | | | | | | | |
| L | * | | * * | | | • | | | | | | | | | |
| L | * | | * | * | | | | | | | | | | | |

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

| | OG FL RAGE | | | | MHC NMOG or | o Particulate matter for meaching adjusting it lacter 23 D [0/(est)=23 day | | | | | | | | | | | |
|--------------|---------------|---|---------------------------|----------------|-------------------------|--|------------|--------------|---------------------------|----------------------|----------------|---------------------------|-------------|-------------------------------|-------------|---------------------|--|
| CERT | | STD | NMOG | NMHC | | mg=millig | or-soak Kr | . [g/m/]=run | ning loss 000 miles | ORVE | ≺ {g/gallor | n dispensed] ahrenheit | =on-board : | refueling vap piemental fe | or recovery | q=qram | |
| * | | * | CERT [g/mi] | CERT [g/mi] | [g/mi] | | [g/mi] | NO | x [g/mi] | | | [mg/mi] | | g/mi] | | x [g/mi] | |
| | | | | | | CERT | STD | CERT | STI | 0 | CERT | STD | CERT | STD | CERT | STD | |
| | | @ 50K | 0.076 | * | 0.117 | 4.0 | 5.0 | 0.3 | 0.6 | 3 | 4 | 11 | * | * | 0.2 | 1.2 | |
| | | @ UL | 0.084 | * | 0.167 | 4.7 | 7.3 | 0.3 | 0.9 |) | 4 | 16 | * | * | 0.3 | 1.8 | |
| | @ 50 | °F & 4K * | | • | * | * | | * | * | | * | * | * | * | * | * | |
| CO [@ 20 | °F& | SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV) | | | | | CO [g | | NMHC+NOx [g/mi] [US06] | | | CO [g/mi] [US06] | | NMHC+NOx [g/mi] [SC03] | | CO [g/mi] [SC03] | |
| 50 | 50K | | SFTP 2 = @ UL (Tier 1, TL | | CERT | STD | CERT | STD | CERT | ST | D CE | RT ST | CER | T STD | CERT | STD | |
| CERT | * | | 152 | SFTP 1 | * | * | • | * | * | * | , | | * | * | * | * | |
| STD | * | | 365 146 | SFTP 2 | * | * | * | * | * | - | - | | * | * | • | | |
| @ UL | | VAPOR | ATIVE FAN | ILY 1 | EVAPORATIVE FAMILY 2 EV | | | | EVA | EVAPORATIVE FAMILY 3 | | | | EVAPORATIVE FAMILY 4 | | | |
| | 3-D | 2-0 | RL | ORVR | 3-D | 2-D | RL | ORVR | 3-D | 2-D | RL | ORVI | | 2-D | RL | ORVR | |
| CERT | * | * | * | * | * | * | * | • | * | * | * | * | * | + | * | * | |
| STD | * | * | * | * | * | * | * | • | * | * | * | * | * | + | | | |

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of October 2002.

Allen yons, Chief

Mobile Source Operations Division