## **HYUNDAI MOTOR COMPANY**

EXECUTIVE ORDER A-254-0082
New Passenger Cars, Light-Duty Trucks
and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

	MODEL YEAR TEST GRO			VEHICLE TYPE		EXHAUST EMISSION TANDARD CATEGOR		EXHAUST / EVAPORATIVE	FUEL TYPE					
2003	знух	3HYXV02.7KLS		Passenger Car		LEV		USEFUL LIFE (UL) (miles)	Gasoline (Indolene)					
					ĺ			100K / 100K						
No.	EVAPOR FAMILY (		No.	SPECIAL FEATUR EMISSION CONTROL SYS		TWC=3-way catalyst ADSTWC=adsorbing TWC WU= warm-up catalyst OC=oxidizing catalyst O2S=oxygen								
1	3HYXR01	34PER	1	2HO2S(2), 2WUT	WC, TWC, SFI,	OBD (F)	sens	or HO2S=heated O	O2S AFS/HAFS=air- fuel ratio					
2	*	*			*	sensor/heated AFS EGR=exhaust gas recirculation AIR=secondary air injection PAIR=pulsed AIR MFI=								
3	*		3		*		thro	multiport fuel injection SFI= sequential MFI TBI= throttle body injection TC/SC = turbo/super charger						
4	*		4		*	CAC=charge air cooler OBD (F) / (P)=full/partial on- board diagnostic prefix 2=parallel (2) suffix=series								
EVAF		ENGINE		VEHICLE	<b>VEHICLES SUB</b>	JECT TO SFTP			ick /C/ = Chevrolet /CD/ =					
No.	No.	SIZE (L	)	MAKES & MODELS	STANDARDS A	RE UNDERLINED	Cadilla	c /G/ = GMC /O/ =	Oldsmobile /P/ = Pontiac					
1	1	2.7		Hyundai Tiburon										
*	•	•												
•	*	*				*								
*	•					*								

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows, except that compliance with the 50° Fahrenheit testing requirement (for low emission vehicles only) may have been met based on the manufacturer's submitted compliance plan in lieu of actual testing. Any debit in the manufacturer's compliance plan for "NMOG Fleet Average" (passenger cars and light-duty trucks) or "Vehicle Equivalent Credit" (medium-duty vehicles) shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the emission standards and certification levels in parentheses are those applicable to testing on gasoline test fuel.)

AVERAGE [g/mi]			NMOG @ RAF=1.00 CH4 RAF = *		NMOG CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxic NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment									oxide ent factor				
CERT	STD	NMO	- 1	NMHC	NMHC	CO [g/mi]		NOx [g/mi]			HCHO [mg/mi]			PM [g/mi]		Hwy NOx [g/mi]		
0.052	0.062	CER [g/m	!	CERT [g/mi]	STD [g/mi]	CERT STD		CE	CERT ST			CERT		TD CERT		STD	CERT	STD
K = 1000 miles	@ 50K	0.02	1	*	0.075	75 0.3		. 0.1		0.2	2 0.2		15	15		*	0.03	0.3
	@ UL	0.02	7	•	0.090	0.4	4.2	4.2 0.2		0.3	0.4		18	1	*	*	0.04	0.4
@ 50°F & 4K		0.08	3	*	0.150	0.4	3.4	0.	01	0.2	0.2 3		30	•		*	*	*
CO [g/mi] @ 20°F & 50K			g = gram mg = milligram		NMHC+NOx [g/mi] NM (composite)		HC+NOx [g/mi] [US06]			CO [g/mi] N		NMHC+NOx [g/mi]		CO [g/mi] [SC03]				
CERT	CERT STD		mi=	mile	CERT	T STD		CERT S		TD CERT		STD				STD	CERT	STD
3.1	3.1 10.0		s	FTP @ 4K	*	•		.04	0.14		3.4 8.0		3.0	0.02		0.20	0.6	2,7
F = degree Fahrenhei		it	S	FTP @ UL	*	*		*	•		*	<del> </del>	•	*		•	*	
@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2					EVA	EVAPORATIVE FAMILY 3					TIVE FAM	ILY 4	
	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORV	R	3-D	2-D	R	L C	RVR	3-D	2-D	RL	ORVR
CERT	0.8	1.1	0.03	0.06	*	*	*	*		•	*	,		*	*		*	•
STD	2.0	2.5	0.05	0.20		•	•	•		•	*	١,	* *		*	*	•	*
2-D, 3-D [g	/test] = 2-da	ay, 3-day	diurnal	and hot-soa	k	RL [g/mi]	= runnir	ig loss		O O	RVR [g/g	allon (	of fuel di	spense	d] = on-	board ref	ueling vapor	recovery

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [labeling], 1968.1 or 1968.1(m)(6.2)[on-board diagnostic (OBD) full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 20 th

\_ day of December 2001.

R. B. Summerfield, Chief Mobile Source Operations Division