

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

**IT IS ORDERED AND RESOLVED:** That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP	VEHICLE TYPE (PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)	EXHAUST EMISSION STANDARD CATEGORY	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas)
2003	3DSXV03.0GNS	PC	Low Emission Vehicle (LEV)	100K / 100K	Gasoline
No.	EVAPORATIVE FAMILY (EVAP)	No.	SPECIAL FEATURES & EMISSION CONTROL SYSTEMS (ECS)	* = not applicable	
1	3DSXR0165A1F	1	TWC, 2WUTWC, 2HO2S(2), EGR, SFI, OBD (F)	TWC=3-way catalyst ADSTWC=adsorbing TWC WU=warm-up catalyst OC=oxidizing catalyst O2S=oxygen sensor HO2S=heated O2S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR=secondary air injection PAIR=pulsed AIR MFI=multiport fuel injection SFI=sequential MFI TBI=throttle body injection TC/SC = turbo/super charger CAC=charge air cooler OBD (F) / (P)=full/partial on-board diagnostic prefix 2=parallel (2) suffix=series	
2	*	2	*		
3	*	3	*		
4	*	4	*		
EVAP No.	ECS No.	ENGINE SIZE (L)	VEHICLE MAKES & MODELS	VEHICLES SUBJECT TO SFTP STANDARDS ARE UNDERLINED	ABBREVIATIONS: /B/ = Buick /C/ = Chevrolet /CD/ = Cadillac /G/ = GMC /O/ = Oldsmobile /P/ = Pontiac
1	1	3.0	<u>Mitsubishi Eclipse, Eclipse Spyder, Galant; Chrysler Sebring; Dodge Stratus</u>		
*	*	*	*		
*	*	*	*		
*	*	*	*		


The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50° Fahrenheit testing requirement (low emission vehicles only) may have been met based on the manufacturer's submitted compliance plan in lieu of actual testing). Any debit in the manufacturer's "NMOG Fleet Average" (passenger cars and light-duty trucks) or "Vehicle Equivalent Credit" (medium-duty vehicles) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the emission standards and certification levels in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]		NMOG @ RAF=0.94 CH4 RAF = *		NMOG or NMHC STD [g/mi]	CH4=methane NOx=oxides of nitrogen		NMOG=non-CH4 organic gas HCHO=formaldehyde		NMHC=non-CH4 hydrocarbon		CO=carbon monoxide		PM=particulate matter		RAF=reactivity adjustment factor								
CERT	STD	NMOG CERT [g/mi]	NMHC CERT [g/mi]		CO [g/mi]	NOx [g/mi]	HCHO [mg/mi]	PM [g/mi]	Hwy NOx [g/mi]														
0.060	0.062				CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD							
K = 1000 miles	@ 50K	0.053	*	0.075	0.4	3.4	0.1	0.2	1	15	*	*	0.03	0.3									
	@ UL	0.070	*	0.090	0.5	4.2	0.1	0.3	2	18	*	*	0.05	0.4									
	@ 50°F & 4K	0.107	*	0.150	0.9	3.4	0.05	0.2	1	30	*	*	*	*									
CO [g/mi] @ 20°F & 50K		g = gram mg = milligram mi = mile		NMHC+NOx [g/mi] (composite)		NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]											
CERT	STD			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD										
5.2	10.0	SFTP @ 4K		*	*	0.07	0.14	1.0	8.0	0.08	0.20	0.3	2.7										
F = degree Fahrenheit		SFTP @ UL		*	*	*	*	*	*	*	*	*	*										
@ UL				EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				EVAPORATIVE FAMILY 4							
3-D		2-D		RL		ORVR		3-D		2-D		RL		ORVR		3-D		2-D		RL		ORVR	
CERT		0.6		0.8		0.01		0.01		*		*		*		*		*		*		*	
STD		2.0		2.5		0.05		0.20		*		*		*		*		*		*		*	
2-D, 3-D [g/test] = 2-day, 3-day diurnal and hot-soak				RL [g/mi] = running loss				ORVR [g/gallon of fuel dispensed] = on-board refueling vapor recovery															

**BE IT FURTHER RESOLVED:** That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [labeling], 1968.1 or 1968.1(m)(6.2)[on-board diagnostic (OBD) full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 15<sup>th</sup> day of January 2002.

  
R. B. Summerfield, Chief  
Mobile Source Operations Division