Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODE		TEST GROUP			VEHICLE TYPE PC=passenger car; LDT=light-duty MDV=medium-duty vehicle; LVW= vehicle weight; ALVW=adjusted	truck; (EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV)			EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)			
2003		3ADXV02.8334		4	PC		LEV			100K / 100K	Gasoline (Indolene)			
No.	EVAPORATIVE FAMILY (EVAF)			No.	SPECIAL FEAT EMISSION CONTROL	URES & SYSTEMS	(ECS)	* = not applicable	OC WI	OC/TWC=oxidizing/3-way cat. ADSTWC=adsor WU= warm-up cat. O2S/HO2S=oxygen sensor/h				
1	3AD	XR014	10232	_ 1	2TWC(2), 21	102S(2), S	FI, AIR, OBD	∥Ar	5/MAF5=air-tuel ratio s	ensor/heated AFS_EGR=avhauer				
2	3ADXR0140233			2	•					gas recirculation AlR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI If BI= throttle body injection, TC/SC=turbo (super-secondary)				
3		*			*									
4		*		4		*		CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
EVAF No.		CS No.	ENGINI SIZE (L		VEHICLE MAKES & MODELS	VEHIC STAND	LES SUBJE	CT TO SFTP UNDERLINED	ABBR	REVIATIONS: *				
1		1	2.8		VOLKSWAGEN: PASSAT / PASSAT VARIANT									
2		1	2.8		V	OLKSWAG	AGEN: PASSAT 4MOTION / PASSAT VARIANT 4MOTION							
*		*	*		*									
*	*		*		*									

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bidual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET AVERAGE [g/mi] CERT STD 0.056 0.062		ET /mi]	NMOG @ RAF= * CH4 RAF = *		NMOG or	CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diutmal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram mo=milligram mi=mile K=1000 miles											
L			TD	NMOG	NMHC CERT [g/mi]	NMHC STD [g/mi]	diurnal+ho mg=milligi	n-suar R	ı. [y/mı]−rur	nning lòss 000 miles	ORVR	g/gallon	dispensed]=	on-board ref	ueling var	Of recovery	g=gram	
			062	CERT [g/mi]				[g/mi]	NO	x [g/mi]	Н	CHO [r	[mg/mi]	SFTP=supple PM [g/	mi]	Hwy NO		
200.00	9 62	9000			15)		CERT	STD	CERT	STI	D CI	ERT	STD	CERT	STD	CERT	STD	
			@ 50K	0.052	*	0.075	0.4	3.4	0.1	0.2	:	1	15	*	•	0.01	0.3	
1 🖺	1	Annual Control	@ UL	0.062	*	0.090	0.6	4.2	0.1	0.3		1	18	•	*	0.02	0.4	
_		@ 50°F	& 4K	0.060	*	0.150	0.4	3.4	0.1	0.2		0.4	30	•	*	*	*	
1 '	@ 20°F & 📳			= @ 4K (SULI V) or 50K (Tid	er 1, TLEV)	NMHC+NOx [g/mi] (composite)		CO [g/mi] (composite)			NMHC+NOx [g/mi] [US06]		O [g/mi] [US06]	NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
	_50H		SFIP 2 =	@ UL (Tier	i, TLEV)	CERT	STD	CERT	STD	CERT	STD	CER			STD	CERT	STD	
-	RT	2.0		profes	SFTP 1	*	*	*	*	0.04	0.14	0.1	8.0	0.01	0.20	0.03	2.7	
S	TD	10.0		尼亚	SFTP 2	•	*	*	•	*	*	•	•	*			*	
@	UL -	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2				EVA	PORATI	/E FAN	AILY 3	FV/	EVAPORATIVE FAMILY 4			
L		3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR					
CE	RT	1.2	1.3	0.00	0.13	1.2	1.3	0.00	0.03	*	*	KL.	URVR	3-D	2-D	RL	ORVR	
ST	D	2.0	2.5	0.05	0.20	2.0	2.5	0.05	0.20	•	*	•	 	+	*	<u> </u>	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of May 2002.

Allen Lyons, Chief

New Vehicle / Engine Programs Branch