

KIA MOTORS CORPORATION

EXECUTIVE ORDER A-315-0032 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODI YEA		TEST GROUP			VEHICLE TYPE (PC=passenger car; LDT=light- MDV=medium-duty vehicle; LV vehicle weight; ALVW=adjus	-duty truck; (EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV)			EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200	3 3	3KMXV01.6C01			PC		LEV			100K / 100K	Gasoline (Indolene)				
No.		PORATIVE ILY (EVAF)		No	SPECIAL FI EMISSION CONTRO	EATURES & OL SYSTEMS	(ECS)	* = not applicable	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2						
1	3KMX	XR0100C01			Hos	H02S(2), TWC, SFI, OBD (P)					ensor/heated AFS_EGR=evhauet				
2		*				*					gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI				
3		*		3		*				TBi= throttle body injection TC/SC=turbo /super charger					
4				4		*		CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series							
EVAF No.		ECS ENGINE No. SIZE (L)			VEHICLE MAKES & MODELS			ECT TO SFTP E UNDERLINED	ABBR	EVIATIONS:					
1	1		1.6				Kia Rio				····				
*	* *			*											
. *	1	*	*					*							
*	* *						*								

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	OG F RAGE	LEET [g/mi]	NMOG @ CH4 R	RAF=1.00 AF = *	NMOG or	o adjustition is a local trial adjust											
CER	T	STD	Time of Minito		NMHC STD	mg≂milligi	X-SOSK KI	. įg/mij=rur	nning loss 000 miles	ORVR	g/gallor	i dispensed] ahrenheit	=on-board r	efueling vap plemental fe	or recovery	g≖gram	
0.062	2	0.062	CERT [g/mi]	CERT [g/mi]	[g/mi]		CO [g/mi]		NOx [g/mi]		HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]		
				[g/iiii]		CERT	STD	CERT	ST) C	ERT	STD	CERT	STD	CERT	STD	
	100	@ 50K	0.031	*	0.075	0.4	3.4	0.03	0.2		1	15	*	*	0.01	0.3	
		@ UL	0.034	*	0.090	0.5	4.2	0.03	0.3		1	18	*	*	0.02	0.4	
	@ 50	0°F & 4K	0.070	*	0.150	0.6	3.4	0.01	0.2		1	30	*	*	*	*	
CO [@ 20		∭ L	= @ 4K (SUL EV) or 50K (Ti	er 1, TLEV)	NMHC+NOx [g/mi] CO [g (composite) (comp		g/mi] osite)	NMHC+NOx [g/mi] [US06]		1			HC+NOx	CO [g/mi] [SC03]			
50	K	SFTP 2 = @ UL (Tier 1, TLEV)		CERT	STD	CERT	STD	CERT	STD	CE	RT ST			CERT	STD		
CERT	2.6			SFTP 1	*	*	*	.*	0.05	0.14	0.	9 8.0	0.05	0.20	0.9	2.7	
STD	10.0	1	444.14	SFTP 2	*	*	*	*	*	*	-	*		•	•		
@ UL		EVAPOR	ATIVE FAN	ILY 1	EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				E.	EVAPORATIVE FAMILY 4			
	3-D	2-1	D RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVI	R 3-D	2-D	RL	ORVR	
CERT	1.7	1.	4 0.03	0.03	*	*	*	*	*	*		*	*	*	*	*	
STD	2.0	2.	5 0.05	0.20	*	*	*	*	*	*	+ +	+	*	*	+		

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of June 2002.

/Allen Lyons, Chief

Mobile Source Operations Division