

MORGAN MOTOR COMPANY LIMITED

EXECUTIVE ORDER A-352-0002 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA	R	TEST GROUP			VEHICLE TYPE (PC=passenger car; LDT=ilght-duty truc MDV=medium-duty vehicle; LVW=loade vehicle weight; ALVW=adjusted LVW)	k; STAN d (LEV=low transition	AUST EMISSION DARD CATEGOR\ emission vehicle; TLI al LEV; ULEV≖ultra L LEV=super ULEV)	EV≖	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)			
200	3	3MMYV04.0MA3			PC	PC TLEV				Gasoline (Indolene)			
No.		APORATIVE No.			SPECIAL FEATURES EMISSION CONTROL SYSTE		,	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S MFI / SFI = multiport fuel injection / sequential MFI					
1	3MMY	MYR0124MA3 📳 1			2TWC, 2HO2S	2), SFI, OBD (F							
2		* 2				*		OBD (F) / (P) = tu prefix 2 = para	il / partial on-board diagnostic allei (2) suffix = series				
EVAI No.		CS lo.	ENGIN SIZE (VEHICLE VE								
1		1	4.0		Morgan Plus Eight								

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	OG FL RAGE		NMOG @ RAF = 1.00 CH4 RAF = *		NMOG or	I OI HILFOGE	I HUHUS	TORMAIGER	/GA PMær	monte	ilata matta	n-CH4 hydro r RAF=read	-thrifts adisse	mant faster	2/2 D I-4-	
CER	T	STD NMOG NMHC		NMHC	dlurnal+ho mg=milligi	it-soak K	ւ [ց/mi]≖ru	nning loss 1000 miles	ORV	R [g/gallor	n dispensed] Fahrenheit	≖on-board r	efueling var piemental fo	or recovery	g≡gram	
0.12	125 0.075		CERT [g/mi]	CERT [g/mi]	[g/mi]		[g/mi]		x [g/mi]		НСНО	[mg/mi]	PM (c			x [g/mi]
AND DEPARTMENT	WARREST AND BUILDING		[Aviii]	[Aum]		CERT	STD	CER	r sti	D	CERT	STD	CERT	STD	CERT	STD
	7	@ 50K	0.117	*	0.125	2.5	3.4	0.2	0.4	1	5	15	*		0.02	0.5
		@ UL	0.131		0.156	3.3	4.2	0.2	0.6	3	5	18	*	*	0.03	0.8
	@ 50	°F & 4K	0.15	*	0.25	2.8	3.4	0.2	0.4		5	30	*	*	*	*
	@ ZU°ro⊾ 🕍		= @ 4K (SUL V) or 50K (Ti	er 1, (LEV)∟	NMHC+NC (compo				NMHC+NC [g/mi] [USC				NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
50			= @ UL (Tier	1, TLEV)	CERT	STD	CERT	STD	CERT	ST	D CE	RT ST			CERT	STD
CERT	6.4			SFTP 1	*	*	•	•	*	*		• •	•	*	•	•
STD	10.0			SFTP 2	*	*	*	•	•	*	,			*	*	•
@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2			EVAPORATIVE FAMILY 3			EVAPORATIVE FAMILY 4					
	3-D	2-[ORVR	3-D	2-D	RL	ORVR	3-D	2-D				2-D	RL	ORVR
CERT	1.7	2.2	0.01	0.19	*	*	*	*	*	*	•	*	*	+	•	*
STD	2.0	2.5	0.05	0.20	*	*	*	*	*	*	*	*	*	•	+ •	•

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.1(m)(6.2) (malfunction and diagnostic system) because the on-board diagnostic II system of the listed vehicle models has been determined to have nine deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of two hundred seventy-five dollars (\$275) per vehicle for the third through ninth deficiencies in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2003 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$5000 per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 2157 day of July 2003.

Allen Lyons, Chief

Mobile Source Operations Division