

ALPINA BURKARD BOVENSIEPEN GmbH + Co.

EXECUTIVE ORDER A-353-0001 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP			ME	VEHICLE TYPE =passenger car; LDT=light-dut; DV=medium-duty vehicle; LVW= ehicle weight; ALVW=adjusted	CATEGOR' vehicle: 1	EMISSION STAND ((LEV=low emi 'LEV= transitional LE' LEV; SULEV=super U	ssion V:	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)			
200	3	3ABBV04.8F51				PC TLEV					100K / 100K	Gasoline		
No.		EVAPORATIVE No.				SPECIAL FEAT EMISSION CONTROL			* = not applicable	cat. ADSTWC=adsorbing TWC HO2S=oxygen sensor/heated O2S				
1	3AB	ABBR0136E46			1	2TWC, 2HO)2S(2), S	FI, AIR, OBD	■ AFS/HAFS=air-fuel ratio sensor/heated AFS					
2		•			2		*		EGR=exhaust gas recirculation AIR=secondary air injection MFI/SFI= multiport fuel injection/sequential MFI					
3		*			3	*					OBD (F) / (P)=full /p prefix 2=parall	eartial on-board diagnostic el (2) suffix=series		
EVAI No.		ECS ENGINE VEHICLE VEH		HICLES SUBJECT TO SETP NDARDS ARE UNDERLINED			ABBREVIATIONS:							
1		1	4.8			ALPINA: BMW/ALPINA ROADSTER V8								
*		*	*						*		· · · · · · · · · · · · · · · · · · ·			

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	33 EL																
AVE	OG FL RAGE	EE I [g/mi]	NMOG @ 1	RAF = 0.98 AF = *	NMOG or	1 Of Nitroge	n mcmo=	rormaidenv	/de PMzr	narticul:	ate matte	· PAEzras	carbons C	temant faster	2/2 D I-/4-		
CER	Т	1111110		NMHC	mg=millig	ram mi=	∟(g/mij≖ru: :mile K=	nning loss 1000 miles	ORVR	₹ [g/gallor •degrees i	i dispensed) Pahrenheit	=on-board i SFTP=sur	efueling vap piemental fe	or recovery	g=gram rocedure		
0.12	125 0.075		CERT [g/mi]	CERT [g/mi]	[g/mi]		[g/mi]		NOx [g/mi]		HCHO [mg/mi]		PM [iOx [g/mi]	
and the second section	Transactors, Supports		[Buni	[Sum]		CERT	STD	CERT	STI)	CERT	STD	CERT	STD	CERT	STD	
		@ 50K	0.080	*	0.125	1.5	3.4	0.1	0.4)	3	15	*	٠	0.02	0.5	
		@ UL	0.091	*	0.156	1.8	4.2	0.1	0.6		4	18	•	*	0.02	0.8	
	@ 50	°F & 4K	0.12	*	0.25	1.4	3.4	0.1	0.4		2	30	*	•	*	*	
@ 20		S LI	= @ 4K (SUL EV) or 50K (Ti	ier 1, TLEV)	NMHC+NC (compo				NMHC+N [g/mi] [US					HC+NOx ni] [SC03]		[g/mi] C03]	
50	50K		≖ @ UL (Tier	UL (Tier 1, TLEV)		STD	CERT	STD	CERT	STI	D CE	RT ST	D CER	T STD	CERT	STD	
CERT	1.3	建和 题		SFTP 1	*	*	•	*	*					•	•	*	
STD	10.0			SFTP 2	*	*	•	•	*	•		• •	•	*	+	*	
@ UL		VAPOR	ATIVE FAN	IILY 1	EVAPORATIVE FAMILY 2				EVA	EVAPORATIVE FAMILY 3				EVAPORATIVE FAMILY 4			
	3-D	2-[RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORV	R 3-D	2-D	RL	ORVR	
CERT	1.1	1.9	0.02	0.10	•	*	•	•	•	*	*	*	- •	•	+	*	
STD	2.0	2.5	0.05	0.20	*	*	*	*	*		*	- .	*	-	*	-	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.1(m)(6.2) (malfunction and diagnostic system) because the on-board diagnostic II system of the listed vehicle models has been determined to have three deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of twenty-five dollars (\$25) per vehicle for the third deficiency in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2003 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$5000 per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

_ day of February 2003.

Aller Lyons, Chief

Mobile Source Operations Division