## California Environmental Protection Agency AIR RESOURCES BOARD

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

	MODEL TEST GROU			Р	MDV=n	VEHICLE TYPE senger car; LDT=light-duty truci edium-duty vehicle; LVW=loade e weight; ALVW=adjusted LVW)	<pre>c; CATEGOF d vehicle;</pre>	EMISSION STANE RY (LEV=low em TLEV= transitional LE LEV; SULEV=super L	ission V:	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200	-		V03.6LE	v	V PC			LEV		100K / 100K	Gasoline (Indolene)				
No.		APORATIVE /IILY (EVAF)		No	».	SPECIAL FEATURE EMISSION CONTROL SYS	S & FEMS (ECS)	* = not applicabl	e O	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing T WU= warm-up cat. O2S/HO2S=oxygen sensor/heated					
1	3FE>	XR0203360				2TWC, 2WUTWC, 2H			-S/HAFS=air-fuel ratio s	ensor/heated AFS_FGR=avhauet					
2		*					*	- Iga	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=paraliae (2) suffix=series						
3		•					*	TE							
4		*				······································	*								
EVAI No.	ECS ENGINE No. SIZE (L)			MA	VEHICLE	EHICLES SUB	JECT TO SFTP	ABB	ABBREVIATIONS:						
1		1 3.6				Ferrari: 360 Modena, 360 Spider									
*		* *				*									
*		*	*												
*		* *						*							

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET NMOG @ RAF=1.00 AVERAGE [g/mi] CH4 RAF = *				NMOG or	Indouen	nunu=ro	rmaidenvoi	a PMZna	rticulate	matter	PAE=roactia	rbon CO=ca vity adjustme	mt fantan f	10 D L-44	3-0/0 1-
CER	CERT STD NMOG		NMHC	NMHC STD	mg=millig	n-suak n	i⊂ (g/mi)≁ru	nning los: 1000 miles	S URVE	(g/gallor	i dispensed] ahrenheit	=on-board re SFTP=supp	efueling vap	of recovery	d≈oram	
0.09			CERT [g/mi]	CERT [g/mi]	[g/mi]		[g/mi]	N(	Dx [g/mi]			mg/mi]	PM [g	/mi]	Hwy NO	
			[8,111]			CERT	STD	CER	T ST	D	CERT	STD	CERT	STD	CERT	STD
		@ 50K	0.050	*	0.075	0.2	3.4	0.2	0.	2	1	15	*	*	0.02	0.3
		@ UL	0.065	*	0.090	0.3	4.2	0.2	0.	3	1	18	*	*	0.02	0.4
	@ 50	°F & 4K	0.042	*	0.150	0.2	3.4	0.1	0.	2	0.5	30	*	•	+	*
@ 20				or 50K (Tier 1, TLEV) (compo					NMHC+NOx [g/mi] [US06]					IC+NOx	CO [g/mi] [SC03]	
50	50K		SFTP 2 = @ UL (Tier 1, TLEV)		CERT	STD	CERT	STD	CERT	ST	DCE	RT STI	CERT	STD	CERT	STD
CERT	4.4		1.1.1	SFTP 1	•	*	*	*	*			*	*	*	*	*
STD	10.0			SFTP 2	*	*	*	*	*	+		*	*	•	+	*
@ UL	E	VAPOR	ATIVE FAI	MILY 1	EVAPORATIVE FAMILY 2			EVAPORATIVE FAMILY 3				EVAPORATIVE FAMILY 4				
_	3-D	2-0	D RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORV		2-D	RL	ORVR
CERT	1.0	1.0	0.03	0.09	*	*	*	*	*	*	*	*	*	*	+	*
STD	2.0	2.5	5 0.05	0.20	*	*	*	*	*	*	*	•	*	*	*	*

**BE IT FURTHER RESOLVED**: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_ day of October 2002.

Aller Lyons, Chief Mobile Source Operations Division