

#### GENERAL MOTORS CORPORATION

**EXECUTIVE ORDER A-006-1168-1** 

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

#### IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	EAR LEST GROUP VEHICLE TYPE		EXHAUST EMISSION STANDARD CATEGORY	STANDARD CATEGORY (miles)				FUEL TYPE			
2004	4GMXT02.8189	LDT: 3751-5750 Pounds LVW	USEPA Bin 9a (opt)	EXH / ORVR	EVAP	EXH	EVAP	Gasoline (Tier 2			
Angelo Marine			Counted as ARB ULÉV	100K	100K	•		Unleaded)			
No.		SPECIAL FEATURES	EVAPORATIVE	FAMILY (EV	AF)	The second second		EMENT (L)			
1	WU-TWC,TV	VC, HO2S(2), SFI, OBD(F)	4GMXR0					22.11 (C)			
•											
*		*	- <u> </u>	•				<b>2.8</b>			
		*									

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

#### BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

#### BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

#### BE IT FURTHER RESOLVED:

The listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-006-1168 dated August 27, 2003.

Executed at El Monte, California on this 29th day of November 2004.

Allen Lyons, Chief

Mobife Source Operations Division

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

### **ATTACHMENT**

# EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

AVERAG			g KAF=" RAF = "	NMOG or	HCHO=form	ane; NMOG≠ naldehyde; P	non-CH4 org M=particulat	anic gas; Ni e matter: RA	MHC≖non-CH	4 hydrocarb	on; CO=carbo actor; 2/3 D [g/	monoxide;	VOx=oxides of	nitrogen;
CERT	STD	NMOG	NMHC								ictor; 2/3 D (g/ iueling vapor r al test procedu		olumai+ ram; mg≃milliç	ram
0.056	0.085	CERT [g/mi]	CERT [g/mi]	[g/mi]	CU	g/mij	NOx	[g/mi]	HCHO	mental regen [mg/mi]		re g/mil	Hwy NO	x (a/mi)
	@ 50K		[3]		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
		0.065	<u>-</u>	0.100	0.8	3.4	0.1	0.2	*	15.	٠	*	0.03	0.27
	@ UL	0.069	*	0.130	0.9	4.2	0.2	0.3	*	18.			0.09	0.40
<i></i> @	50°F & 4K	*	*	*	*	*	•	*	•	*	*	+	*	+

CO [9	[g/mi] - & 50K		(comp	Ox [g/mi] osite)		g/mi] posite)		C+NOx [US06]	CO [	g/mi] 06]		C+NOx [SC03]	CO	[g/mi] 2031
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
CERT	5.7	SFTP @ 4000 miles	٠	*	*	•	0.08	0.25	0.4	10.5	0.03	0.27	0.2	3.5
STD	12.5	SFTP @ 100000 miles	0.30	1.04	•	*	•	*	2.8	14.6	•	•	1.6	4.9

Evaporative Family		al + Hot Soak est) @ UL		al + Hot Soak est) @ UL		ng Loss nile) @ UL	On-Board Ref Recovery (gram	ueling Vapor s/gallon) @ UL
	CERT	STD	CERT	STD	CERT	STD	CERT	STD
4GMXR0175922	0.5	2.0	0.8	2.5	0.00	0.05	0.14	0,20
*	*	*	*	*	*	•	*	0.20
•	*	*	٠	•	*	*	*	•
*	*	*	•	*	*	*	*	

<sup>\* =</sup> not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck: MDV=medium-duty vehicle; ECS= Emission Control System; STD= Standard; CERT= Certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; TLEV=transitional LEV; ULEV=ultra LEV; SULEV=super ULEV; TWC=3-way catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; OC=oxidizing catalyst; O2S=oxygen sensor; HO2S=heated O2S; AFS/HAFS=air- fuel ratio sensor / heated AFS; EGR=exhaust catalyst; AlR=secondary air injection; PAIR=pulsed AIR; MFI= multiport fuel injection; SFI=sequential MFI; TBI=throttle body injection; TC/SC= turbo/super charger; LPG=liquefied petroleum gas; E85="85%" Ethanol Fuel

## 2004 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	IN-I COMPI (*=N/A or A/E=ext	IEDIATE USE LIANCE full in-use; 1. / evap. ate in-use)	PHASE-IN STD.	OBD II								
					EXH	EVAP										
CHEVROLET	COLORADO 2WD	4GMXR0175922	1	2.8	*	. *	SFTP	Full								
CHEVROLET	COLORADO 4WD	4GMXR0175922	1	2.8	*	•	SFTP	Full								
CHEVROLET	COLORADO CREW CAB 2WD	4GMXR0175922	1	2.8 .	*	*	SFTP	Full								
CHEVROLET	COLORADO CREW CAB 4WD	4GMXR0175922	1	2.8		•	SFTP	Full								
GMC	CANYON 4WD	4GMXR0175922	1	2.8	*	*	SFTP	Full								
GMC	CANYON CREW CAB 4WD	4GMXR0175922	1	2.8	*		SFTP	Full								
GMC	CANYON 2WD	4GMXR0175922	1	2.8	*	*	SFTP	Full								
GMC	CANYON CREW CAB 2WD	4GMXR0175922	1	2.8		*	SFTP									
CHEVROLET	COLORADO CAB CHASSIS INCOMPLETE 2WD	4GMXR0175922	1	2.8	•	-		Full								
GMC	CANYON CAB CHASSIS INCOMPLETE 2WD	4GMXR0175922	1	2.8	•	*	SFTP	Full Full								