

### GENERAL MOTORS CORPORATION

**EXECUTIVE ORDER A-006-1146** 

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

## IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP   VEHICLE TYPE   1		EXHAUST EMISSION STANDARD CATEGORY	USEFU (mil		IN- COMP (*=N/A or A/E=ex	MEDIATE -USE PLIANCE full in-use; th. / evap. late in-use)	FUEL TYPE		
2004	4GMXT04.3184	3751-5750 Pounds Adjusted Loaded Vehicle Weight Medium-	Low Emission Vehicle (LEV)	EXH / ORVR	EVAP	EXH	EVAP	GASOLINE		
Control Control		Duty Vehicle	` ,	120K	150K	*	E	(Tier 2 Unleaded)		
No.	ECS &	SPECIAL FEATURES	EVAPORATIVE				DISPLACE			
1	2TWC, 2	2HO2S(2), SFI, OBD(F)	4GMXE	0111952						
			4GMXE0223956							
*			4GMXE	4GMXE0133954						
*		*	•							

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

#### BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

### **BE IT FURTHER RESOLVED:**

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 18th day of March 2003.

Allen Lyons, Chief

Mobile Source Operations Division

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

## **ATTACHMENT**

# EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	G FLEET AGE [g/mi]		@ RAF=* !AF = *	I MINIOG OF	I UCUO-IOUI	raidenyde; P	'M=particulati	e matter: RA	uh≃reactivity a	adiustment fa	ctor: 2/3 D (a/i	test1=2/3 day	NOx=oxides of	-
CERT	STD	NMOG CERT	NMHC	INMHC	mi=mile; K=	L (g/m+j=runi 1000 miles;	ning loss; OR	VR [g/gallon	1 dispensed]=	on-board ref	ueling vapor real test procedu	ecovery: a=o	ram; <b>mg</b> =millio	ram
		[g/mi]	CERT [g/mi]	[g/mi]	CO	g/mi]	NOx	g/mi]		[mg/mi]	PM [		Hwy NO	x [g/mi]
			[a,,,,,]	<u> </u>	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
	@ 50K	0.085	•	0.160	2.2	4.4	0.2	0.4	*	18.	*	*	0.1	0.8
1	@ UL	0.098	*	0.230	2.7	6.4	0,3	0.6	. •	27.	*	*	0.2	1.2
J. Hy	@ 50°F & 4K	*	*	*	*	*	•	*	*	*	*	*	*	*

	O [g/mi]	The solution of the solution o		Ox [g/mi] osite)		g/mi] posite)		C+NOx [US06]	CO [ US	g/mi] :06]	NMHC [g/mi]	+NOx [SC03]	00 ( cs)	
@ 2	0°F & 50K		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
CERT	3.9	SFTP @ 4000 miles	*	*	*	*	0.04	0.40	2.5	10.5	0.02	0.31	1,1	3.5
STD	12.5	SFTP @ * miles	* ,	*	*	*	*	*	*	*	*		*	*

Evaporative Family	3-Days Diurnal + Hot Soak (grams/test) @ UL		2-Days Diurn (grams/te		Runnin (grams/m		On-Board Refueling Vapor Recovery (grams/gallon) @ UL		
	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
4GMXE0111952	0.78	0.90	0.88	1.15	0.00	0.05	*	*	
4GMXE0223956	0.78	0.90	0.53	1.15	0.00	0.05	*	*	
4GMXE0133954	0.59	0.90	0.56	1.15	0.00	0.05	*	*	
*	*	*	*	*	*	*	*	+	

<sup>\* =</sup> not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; ECS= Emission Control System; STD= Standard; CERT= Certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; TLEV=transitional LEV; ULEV=ultra LEV; SULEV=super ULEV; TWC=3-way catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; OC=oxidizing catalyst; O2S=oxygen sensor; HO2S=heated O2S; AFS/HAFS=air- fuel ratio sensor / heated AFS; EGR=exhaust gas recirculation; AIR=secondary air injection; PAIR=pulsed AIR; MFI= multiport fuel injection; SFI=sequential MFI; TBI=throttle body injection; TC/SC= turbo/super charger; CAC=charge air cooler; OBD (F)/(P)=full/partial on-board diagnostic; DOR=direct ozone reducing; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefled natural gas; LPG=liquefled petroleum gas; E85="85%" Ethanol Fuel;

## 2004 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	IN- COMP (*=N/A or A/E=ex	MEDIATE USE LIANCE full in-use; h. / evap. ate in-use)	PHASE-IN STD.	OBD II
					EXH	EVAP		
CHEVROLET	C1500 SILVERADO 2WD	4GMXE0111952	1	4.3	*	E	SFTP	Full
CHEVROLET	K1500 SILVERADO 4WD	4GMXE0111952	1	4.3	*	E	SFTP	Full
GMC	C1500 SIERRA 2WD	4GMXE0111952	1	4.3	*	E	SFTP	Full
GMC	K1500 SIERRA 4WD	4GMXE0111952	1	4.3	*	E	SFTP	Full
GMC	G15/25 SAVANA 2WD CARGO CONV	4GMXE0223956	1	4.3	*	E	SFTP	Full
GMC	G1500/2500 SAVANA CARGO 2WD	4GMXE0223956	1	4.3	*	E	SFTP	Full
GMC	G1500/2500 SAVANA PASSEN 2WD	4GMXE0223956	1	4.3	*	E	SFTP	Full
CHEVROLET	G1500/2500 CHEVY EXPRESS 2WD	4GMXE0223956	1	4.3	* '	E	SFTP	Full
CHEVROLET	G1500/2500 CHEVY VAN 2WD	4GMXE0223956	1	4.3	*	E	SFTP	Full
CHEVROLET	G15/25 CHEVY VAN 2WD CONV	4GMXE0223956	1	4.3	*	E	SFTP	Full
CHEVROLET	C1500 SILVERADO 2WD	4GMXE0133954	1	4.3	*	E	SFTP	Full
CHEVROLET	K1500 SILVERADO 4WD	4GMXE0133954	1	4.3	*	E	SFTP	Full
GMC ,	C1500 SIERRA 2WD	4GMXE0133954	1	4.3	*	E	SFTP	Full
GMC	K1500 SIERRA 4WD	4GMXE0133954	1	4.3	*	E	SFTP	Full