

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODI YEA		TEST GROUP			VEHICLE TYPE PC=passenger car; LDT=light-duty truck MDV=medium-duty vehicle; LVW≃loaded vehicle weight; ALVW=adjusted LVW)	; CATEGOR vehicle; T ULEV=ultra	TLEV= transitional LEV; LEV; SULEV=super ULE	lon EVAPORATIVE USEFUL LIFE	FUEL TYPE (CNG/LNG=compressed/ ilquefied natural gas; LPG=ilquefied petroleum gas)				
200	4	4FJXV02.5SHU			PC	1) US EPA 2) Counted	i as ARB LEV 1 ULE	/ 100K / 100K	Gasoline (Tier 2 Unleaded)				
No.	EVAPORATIVE FAMILY (EVAF)			No.	SPECIAL FEATURES EMISSION CONTROL SYST		* = not applicable	NWU= warm-up cat. O2S/HO2S=oxygen sensor/heated O					
1	4FJXR01251BB			1	TWC(2), HO2S(2), SFI, EGR, OB		sensor/heated AFS_EGR=exhaust NR=secondary air injection/pulsed					
2	•			2		*	AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board						
3	*			3		•							
4	•			4		•	diagnostic prefix 2=par	allel (2) suffix=series					
EVAI No.			ENGIN SIZE (L				JECT TO SFTP	ABBREVIATIONS:					
1	1 1		2.5		SUBARU: FORESTER AWD								
*	· · ·		丁	•									
*		*	*				*						
*		* *					•						

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]		NMOG @ RAF = * CH4 RAF = *		NMOG or	CH4=methane NMOG=non-CH4 organic gases NMHC=non-CH4 hydrocarbons CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diurnal-hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram												
CER'	Г (STD NMO		NMHC	NMHC	mg=millig	ram mi=	mile K=1	000 miles	F≖deg	rees Fa	hrenheit	SFTP=sup	plemental fe	deral test pr	ocedure	
0.045	5 O	.053	CERT	CERT [g/ml]	[g/mi]		[g/mi]		x [g/mi]		CHO [n		PM [STD	Hwy NO	x (g/mi) STD	
			[g/mi]			CERT	STD	CERT	STE	CE	KI	STD	CERT	310	CERT		
		@ 50K	0.061	*	0.100	1.8	3.4	0.05	0.14	4 ′	1	15	•	*	0.01	0.19	
		@ UL	0.066	*	0.125	2.1	4.2	0.06	0.20	0 ′	1	18	*	*	0.01	0.27	
	@ 50°	F & 4K	+	•	•	•	*	*	*	1	•	*	*	*	*	*	
	CO [g/mi] @ 20°F &		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)		NMHC+NOx [g/mi] CO [g/mi] (composite) (composite				NMHC+NOx				NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
50K		SFTP 2 = @ UL (TI			CERT	STD	CERT	STD	CERT	STD	CEF	RT STE	CER	T STD	CERT	STD	
CERT	4.5			SFTP 1	*	*	*	*	0.06	0.14	4.5	8.0	0.13	0.20	1.6	2.7	
STD	10.0			SFTP 2	0.13	0.71	*	*	•	*	6.1	11.	1 *	*	2.1	3.7	
@ UL	Ε	VAPOR	ATIVE FAI	VILY 1	EVA	EVAPORATIVE FAMILY 2 EVAPO				PORATIVE FAMILY 3			E	EVAPORATIVE FAMILY 4			
	3-D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVI	R 3-D	2-D	RL	ORVR	
CERT	1.1	1.1	0.00	0.02	*	*	*	*	*	*	*	*	*	•	*	*	
STD	2.0	2.5	5 0.05	0.20	•	*	*	*	*	*	*	*	*	*	*	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

Raphael Surrount

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of December 2002.

Allen Lyons, Chief

Mobile Source Operations Division