

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD! YEA		TEST GROUP			M	VEHICLE TYPE E-passenger car; LDT=light-duty tr DV=medium-duty vehicle; LVW=loa ehicle welght; ALVW=adjusted LVV	EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV)			EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200	4	4MBXV03.7LBI				PC	1) USEPA Bin 8 2) Counted as ARB LEV I ULEV			EXH: 100K EVAF1 & 3/ORVR: 100K EVAF2/ORVR: 150K/100K	NORVR: Gasoline K (Tier 2 Unleaded)				
No.		IPORA IILY (E			No.	SPECIAL FEATUR EMISSION CONTROL SY			е	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O25/HO2S=oxygen sensor/heated O2S					
1	4MB	MBXR0155LNZ			1	SFI, 2WUTWC, 2TWC	, 2HO	2S(2), AIR, E		AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board					
2	4MBXR0165LNC			ľ	2		*								
3	4MB	4MBXR0218LNZ			3		*								
4		*			4	M. M	*	······································	\neg	diagnostic prefix 2=parallel (2) suffix=series					
EVA		ECS ENGINE			VEHICLE			CT TO SFTP	Δ	BBREVIATIONS: *					
No.			SIZE (L	-)		MAKES & MODELS	LES & MODELS STANDARDS ARE UNDERLINED								
1		1	3.2				MER	RCEDES-BEN	tible	e, CLK320 Coupe					
2		1	3.2			MERCEDES-BENZ E320, E320 4Matic, E320 (WAGON), E320 4Matic (WAGON)									
3	1 3.7					MERCEDES-BENZ S350									
*	* *					*									

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]			NMOG @ CH4 R) RAF= * AF = *	NMOG or	CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram											
CER	ERT STD		NMOG			mg=milli	gram mi:	∟lg/mij=ru =mile K=	nning los 1000 mile:	s ORVR[s F=de	g/gallon grees Fa	aispensea _. ahrenheit	on-board r≎ SFTP=sup	etueling vap plemental fe	or recovery deral test pi	g≖gram rocedure	
0.049	9 (0.053	CERT	CERT [g/mi]	STD [g/mi]		CO [g/mi]		NOx [g/mi]		HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]		
0.040			[g/mi]			CERT	STD	CER	T S	rd C	ERT	STD	CERT	STD	CERT	STD	
	(0		0.017	*	0.100	0.2	3.4	0.06	0.	14	1	15	*	*	0.005	0.19	
	@ U		0.019	*	0.125	0.3	4.2	0.06	0.	20	1	18	*	*	0.01	0.27	
	@ 50°	F & 4K	*	*	*	*	*	*	,	•	*	*	*	*	*	*	
CO [@ 20	g/mi] ?F &	SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)				IMHC+NOx [g/mi] CO [g/n (composite) (compos			NMHC+NOx [g/mi] [US06]		(O [g/mi] [US06]		NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
50		SFTP 2 = @ UL (Tier		1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CE	RT ST	D CER	STD	CERT	STD	
CERT	0.6		S	FTP @4K	*	*	*	*	0.07	0.14	1.	5 8.0	0.02	0.20	0.1	2.7	
STD	10.0		SFTP @UL		0.06	0.71	*	*	*	*	1.	7 11.	1 *	*	0.3	3.7	
@ UL	E	VAPOR	ATIVE FAN	IILY 1	EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				E	EVAPORATIVE FAMILY 4			
W OL	3-D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORV	R 3-D	2-D	RL	ORVR	
CERT	0.5	0.6	0.004	0.02	0.34	0.38	0.00	0.05	0.5	1.6	0.00	0.01	*	*	*	*	
STD:	2.0	2.5	0.05	0.20	0.50	0.65	0.05	0.20	2.0	2.5	0.0	0.20	*	*	*	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: The listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order. This Executive Order hereby supersedes Executive Order A-003-0271 dated June 26, 2003.

Executed at El Monte, California on this _______ day of November 2003.

Allen yons, Chief

Mobile Source Operations Division