

## GENERAL MOTORS CORPORATION

EXECUTIVE ORDER A-006-1170 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODI	R	TEST GROUP			VEHICLE TYPE (PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)			CATEGOR vehicle; ULEV=ultra	TLEV= transitional LE LEV; SULEV=super t	ission V:		FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)			
2004		4GMXV02.0002			PC			1) USEPA E 2) Counted	3in 8 as ARB LEV I ULE	EV	100K / 100K	Gasoline (Indolene)			
No.	FAM	PORA ILY (E	VAF)	N	).	SPECIAL FEAT EMISSION CONTROL	URES SYSTE	8.	* = not applicabl	<b>e</b> 0	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TW WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O				
1	4GM	XR013	33910	<u>_</u> 1		SFI, TWC, H	O2S(2),	TC, CAC, OE	3D (F)	BIA	ro/HArozair-fuel ratio s	Ansor/heated AES ECO-cube 1			
2		*					*			gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series					
3		*					+		TI						
4		*					*								
EVAF No.		No. SI			М	VEHICLE AKES & MODELS	VE	HCLES SUBJ	ECT TO SFTP E UNDERLINED	- Ki	REVIATIONS: *				
1		1	2.0			Saab: 9-3 Sport Sedan, 9-3 Convertible									
*		*				*									
*		*	*						*						
*	*		•		*										

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

AVE	NMOG FLEET NMOG @ RAF= * AVERAGE [g/mi] CH4 RAF = *					NMOG or							H4 hydroca RAF=reactiv				
CER	RT STD		NMOG NMHC CERT CERT			NMHC	mg=milli	gram mi	ու [Թուու]–ւ	inning los 1000 mile	S UKV	rk [g/gallor	dispensed]	≖on-board r	efueling vap plemental fe	or recovery	g≅gram
0.05	2 0	0.053	[g/mi] [g/m		CERT [a/mi]	[g/mi]		[g/mi]		Ox [g/mi			[mg/mi]		g/mi]	Hwy NO	
					[9/111]		CERT	STD	CER	TS	TD	CERT	STD	CERT	STD	CERT	STD
	(A + L	@ 50K		<del> </del>		0.100	1.0	3.4	0.05	0.	14	٠	15	*	*	0.03	0.19
	4.1	@ UL 0.05		52	*	0.125	1.4	4.2	0.08	0.	0.20 *		18	*	*	0.05	0.27
	@ 50°F & 4K		K *		*	*	*	*		,		*	*	*	•	*	*
@ 20	°F&	SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV) SFTP 2 = @ UL (Tier 1, TLEV)			NMHC+NC (compo	osite)	CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]			CO [g/mi] [US06]	NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
50	<u> </u>	orth 7:	- (Ø OL	(I ler 1	, ILEV)	CERT	STD	CERT	STD	CERT	ST	D CE	RT ST			CERT	STD
CERT	2.0	1,111		SF	TP @4K	•	•	*	•	0.02	0.1	14 5.	.3 8.0	0.04	0.20	1.7	2.7
STD	10.0			SFT	@100K	0.12	0.71	*	*	•	*	5.	9 11.	1 *	*	2.4	3.7
@ UL		VAPORA				EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				EVAPORATIVE FAMILY 4			
	3-D	2-D		RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORV		2-D	RL	ORVR
CERT	1.2	1.2		0.00	0.09	*	*	*	*	*	*	*	*	*	+	*	*
STD	2.0	2.5		0.05	0.20	*	*	•	*	•		-		<del></del>	<del></del>	+	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

**BE IT FURTHER RESOLVED:** The listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 25th day of August 2003.

Allen Lyons, Chief

Mobile Source Operations Division