California Environmental Protection Agency **AIR RESOURCES BOARD**

BAYERISCHE MOTOREN WERKE AG

EXECUTIVE ORDER A-008-0163 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP				VEHICLE TYPE C=passenger car; LDT=light-duty ack; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)	EXHAUST EN STANDARD CA (LEV=low emission TLEV= transition ULEV=ultra SULEV=super	ATEGORY on vehicle; nal LEV; LEV;		(HAUST & ORVR / EVAPORATIVE FUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)			
200	<u> </u>	4BMXV03.0LER			PC	LEV			0K / 100K (EVAF 1) 0K / 150K (EVAF 2)	Gasoline				
No.		APOR/ MILY (E			No.	SPECIAL FEATU EMISSION CONTROL S		* = not app	licable	OC/TWC=oxidizing/3-way	cat. ADSTWC=adsorbing TWC IO2S=oxygen sensor/heated O2S			
1	48N	XR01	36E46	10.000 A	1	2TWC, 2HO2	S(2), SFI, AIR, OBD	MAFS/HAFS=air-fuel ratio s	ensor/heated AFS EGR#exhaust					
2	4BN	AXR0128E85			2		*	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI≖ multiport fuel injection/sequential MFI TBI≖ throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P]=fuil /partial on-board						
3		•			3	4 · · · · · · · · · · · · · · · · · · ·	*							
4		*	*				*	diagnostic prefix 2=para	liel (2) suffix=series					
EVAI No.			ENGINE SIZE (L)			VEHICLE VEHICLES SUBJECT TO SFTP				ABBREVIATIONS:				
1		1	2.5			BMW: 325x1, 325x1 Sport Wagon								
1		1	3.0		BMW 330xi									
2		1	2.5			BMW Z4								
*		*	*		*									

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NM AVE	OG FL RAGE	EET [g/mi]	NMOG @ CH4 R) RAF = * AF = *	NMOG or	CH4=methane NMOG=non-CH4 organic gases NMHC=non-CH4 hydrocarbons CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day											
CER	Т	STD	NMOG NMHC		NMHC STD	diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram mg=milligram mi=mile K=1000 miles F=degrees Fahrenheit SFTP=supplemental federal test procedure											
0.04	8 0	0.053	CERT CERT [g/mi] [g/mi]		[g/mi]	CO [g/mi]			NOx [g/mi]		HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]		
			[Auni	[8,]		CERT	STD	CER	T ST		CERT	STD	CERT	STD	CERT	STD	
		@ 50K	0.018	•	0.075	0.5	3.4	0.1	0.	2	0.2	15	+	*	0.0	0.3	
		@ UL	0.019	*	0.090	0.6	4.2	0.1	0.	3	0.2	18	*	*	0.0	0.4	
	@ 50'	'F & 4K	0.036	*	0.150	0.4	3.4	0.05	0.	2	0.2	30	*	•	*	•	
CO [@ 20	g/mi] °F &	E LE	= @ 4K (SUL V) or 50K (T	NMHC+NC (compo	MHC+NOx [g/mi] CO [g/mi] (composite) (composite)						CO [g/mi] [US06]	NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]			
50	50K		SFTP 2 = @ UL (Tier 1, TLEV)		CERT	STD	CERT	STD	CERT	ST	D CE	RT ST	D CERT	STD	CERT	STD	
CERT	2.1			SFTP 1	•	*	*	*	0.08	0.1	14 0	.7 8.0	0.16	0.20	0.4	2.7	
STD	10.0		an de la compañía de	SFTP 2	*	*	*	*	•	•	,	• •	•	*	•	+	
@ UL	E	VAPORA	ATIVE FAN	IILY 1	EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3			EVAPORATIVE FAMILY 4					
-	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	R	_ ORV	R 3-D	2-D	RL	ORVR	
CERT	1.0	1.9	0.02	0.07	0.45	0.27	0.01	0.06	*	*	*	*	*	*	+	*	
STD	2.0	2.5	0.05	0.20	0.50	0.65	0.05	0.20	*	*	*	*	*	*	*	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of September 2003.

Surnaut

Allen Lyons, Chief \mathcal{O} Mobile Source Operations Division