

BAYERISCHE MOTOREN WERKE AG

EXECUTIVE ORDER A-008-0166-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD		TEST GROUP			(PC=	VEHICLE TYPE -passenger car; LDT=light-duty truck;	EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV)				EFUL LIFE	FUEL TYPE (CNG/LNG=compres sed/ liquefied natural				
YEA	R '				MD\	/=medium-duty vehicle; LVW=loaded				EVAF 1				EVAF 2		
					ve	hicle weight; ALVW=adjusted LVW)				(H	EVAP/ ORVR	EXH/ ORVR	EVAP	gas; LPG=liquefied petroleum gas)		
200	4 46	4BMXV03.0UL2				PC	LEV II ULEV							Gasoline		
										ΣK	100K	120K	150K			
No.	EVAP(FAMIL			No).	SPECIAL FEATURES EMISSION CONTROL SYSTE	& VIS (ECS)	* = not applica	able	ble OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC						
1	1 4BMXR0136E46			1		2TWC, 2HAFS, 2HO2	WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas									
2	4BMXF	BMXR0090R60				*		recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle								
3		*			\top						ly injection	TC/SC=turi	oo /super cl	harger CAC≕charge air		
4		*	*			*		2=p	araliei (2)) / (P)=Tull /Ç suffix=serie	s artial on-bi	oard diagnostic prefix				
EVAI No.	EC:		ENGINI SIZE (L			VEHICLE VEHICLES SUBJECT TO SFTP MAKES & MODELS STANDARDS ARE UNDERLINED ABBREVIATIONS:										
1	1		2.5		BMW: 325i, 325Ci, 325Ci Convertible, 325i Sport Wagon											
1	1		3.0				BMW: 330i, 330Cl, 330Cl Convertible, 330i (Sport Package)									
2	1		2.5			BMW: 525i										
2	1		3.0			BMW: 530i										

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bidual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET NMOG AVERAGE [g/mi] CH4			NMOG @ RAF = * CH4 RAF = *		NMOG or	CH4=methane NMOG=non-CH4 organic gases NMHC=non-CH4 hydrocarbons CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diurnal+hot-soak RL [g/ml]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram										
CER	T S1	ΓD	NMOG NM		NMHC STD	mg=milligra	L-SOAK IKI.	. լg/m:j≂ nur	nning loss	ORVK [g.	/gallon c	lispensed): hrenheit	≐on-board r	efueling vap plemental fe	or recovery	q=qram
0.04	8 0.0	53	CERT [g/mi]	CERT [g/mi]	[g/mi]	CO [x [g/mi]	H	CHO [n	ig/ mi]	PM [Hwy NO	
			[3,,,,,]	farmi		CERT	STD	CERT	STE	CE	RT	STD	CERT	STD	CERT	STD
4	@	50K	0.008	*	0.040	0.5	1.7	0.005	0.0	5	0	8	*	*	0.003	0.07
*		@ UL	0.009	*	0.055	0.5	2.1	0.01	0.07		0	11	*	*	0.004	0.09
	@ 50°F	& 4K	0.014	*	0.080	0.7	1.7	0.01	0.05	5	0	16	*	*	*	*
@ 20	°F&	LEV	@ 4K (SULI) or 50K (Ti	er 1, TLEV)	NMHC+NC (compo								NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
50	K	SFTP 2 = @ UL (Tie		1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CER	T STE	CER	STD	CERT	STD
CERT	1.3		44.0	SFTP 1	•		7	*	0.01	0.14	1.5	8.0	0.00	0.20	0.8	2.7
STD	10.0		學量學	SFTP 2		1		•		*	*	*	*	*	*	*
@ UL			TIVE FAM		EVAPORATIVE FAMILY 2				EVA	PORATIV	E FAN	IILY 3	E	EVAPORATIVE FAMILY 4		
	3-D	2-D	RL	ORVR	3-D	2-D	RL (ORVR	3-D	2-D	RL	ORVE	₹ 3-D	2-D	RL	ORVR
CERT	1.0	1.9	0.02	0.97	0.23	0.31	0.02	0.12	*	*	*	*	*	*	*	·
STD	2.0	2.5	0.05	0.20	0.50	0.65	0.05	0.20	*	*	*	*	*	*	*	•

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are permitted intermediate in-use compliance standards pursuant to 13 CCR Section 1961(a)(10).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-008-0166 dated April 14, 2003.

Executed at El Monte, California on this ______ day of August 2003.

Allen Jons, Chief Mobile Source Operations Division