FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1175-1
New Passenger Cars, Light-Duty Trucks
and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR TEST GROUP					VEHICLE TYPE PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)	CATEGOR'	EMISSION STANDAI Y (LEV=low emissi 'LEV= transitional LEV; LEV; SULEV=super ULE	EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)					
200	2004 4FMXT04.02I				LDT: 3,751 – 5,750 pounds LVW	1) USEPA E 2) Counted	Bin 9a (Opt) as ARB LEV I ULEV	EXH/ORVR: 100K EVAF1: 100K EVAF2:150K	Gasoline (Tier 2 Unleaded)					
No.		EVAPORATIVE FAMILY (EVAF)		No	SPECIAL FEATURES EMISSION CONTROL SYSTE		* = not applicable	Wille warm-up cat. O2S/HO	at. ADSTWC=adsorbing TWC 2S=oxygen sensor/heated O2S					
1	4FMX	4FMXR0165GBE			2TWC, TWC, 2HO2S, H	02S, EGR, SF	AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger							
2	4FMXR0165GBL			2		•								
3	*			3		•	■CAC=charge air cooler OBD (F) / (P)=full /partial on-board							
4						•	diagnostic prefix 2=paralle	ol (2) suffix=series						
EVA No.		CS No.	ENGIN SIZE (I		MAKES & MODELS STA	NDARDS AR	(F ONDEKLINED .	ABBREVIATIONS:	•.					
1	1		4.0		Ford Ranger Pickup 2WD/4WD; Mazda B4000 2WD/4WD									
2	1 4.0			Ford Ranger Pickup 2WD/4WD: Mazda 84000 2WD/4WD										
				•										
			*	_	•									

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]			NMOG @ RAF= * CH4 RAF = *			NMOG or		HCHO	maldabuda	DMenart	iculate ma ORVR [g/	itter R gallon d	AF≖reactiv lispensed]:	bon CO≖ca ity adjustme ≖on-board re	nt ractor 2 fueling vap	or recovery	G≈GLSW l≃5/3 gsA	
CERT	Γ ;	NMOG		NMHC	NMHC	mg≖millig	ram mi≖	mile K≠1	000 miles	F≖deg	rees Fal	hrenheit	SFTP=supp PM [g	emental rec	ierai test pr Hwy NÖ	oceanie		
0.053	s a	.085	CERT [g/mi]		CERT [g/mi]	[g/mi]	CERT	[g/mi] STD	CERT	x (g/mi) STC		RT	STD	CERT	STD	CERT	STD	
S.F.		@ 50K		32	•	0.100	1.5	3.4	0.04	0.2	-	•	15	*	*	0.05	0.27	
		@ UL	0.0	146	*	0.130	2.5	4.2	0.1	0.3		•	18	*	*	80.0	0.40	
	∂ 50°	F & 4K		•	*	*			. *	•		•	*	*	*	*	*	
CO [g/mi]	SFTP 1	SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)		NMHC+NO			NMHC+NOx [g/mi] [US06]			O [g/mi] [US06]		IC+NOx] [SC03]		[g/mi] C03]			
@ 20°F & 50K		SFTP 2	= @:UL (Tier		r 1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CER	T ST	CERT	STD	CERT	STD	
CERT	4.3		and and a	S	FTP @4K	•	*		*	0.05	0.25	4.8	10.	5 0.02	0.27	0.6	3.5	
STD	12.5			SI	FTP @ UL	0.13	1.04	•	*	*	*	6.7	14.	6 *	*	2.5	4.9	
	EVAPORATIVE FAMILY 1					EVA	EVAPORATIVE FAMILY 2			EVAPORATIVE FAMILY 3				E,	EVAPORATIVE FAMILY 4			
@ UL	3-D	2-0		RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORV	R 3-D	2-D	RL	ORVR	
CERT	1.2	1.1		0.01	0.04	0.46	0.36	0.02	0.07	*	*	*	*	*	*	*	<u> </u>	
STD	2.0	2.5		0.05	0.20	0.65	0.85	0.05	0.20	*	*	*	•	*	•	•		

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-010-1175 dated June 30, 2003.

Executed at El Monte, California on this 2014 day of November 2003.

Allen Lyons, Chief

Mobile Source Operations Division