

## DAIMLERCHRYSLER CORPORATION

EXECUTIVE ORDER A-009-0622-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

*	-		•	<del> </del>										
*			*			200 July 240 Avid County 240/Avid								
2	1 3.8		3,8	T	Dodge Caravan 2WD/AWD, Chrysler: Voyager 2WD, Town & Country 2WD/AWD									
1	1 3.5				Chrysler Pacifica, Chrysler Pacifica AWD									
EVAI No.	,	o. SIZE (L)			VEHICLE VEI MAKES & MODELS STA	HICLES SUBJI NDARDS ARE	ABBR	ABBREVIATIONS:						
4	- 1'			4	•			dla	diagnostic prefix 2=parallel (2) suffix=series					
3		*		3			TBI	TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board						
2	4CRXR0	CRXR0177GHA		2			gas AlR	WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/puised AIR MFI/SFI= multiport fuel injection/sequential MFI						
_ 1	4CRXR0177GCA		<u>م</u> ا	1	TWC, SFI, HO2S(	2), EGR, OBD	MAF							
No.	FAMILY	APORATIVE MILY (EVAF)			SPECIAL FEATURES EMISSION CONTROL SYSTE		* = not applicable	OC WI	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorb					
200		4CRXT03.82N0			LDT: 3,751-5,750 pounds LVW	1) USEPA Bin 9a (Opt) 2) Counted as ARB LEV I ULEV			EXH/ORVR: 100K EVAF1: 100K EVAF2: 150K	Gasoline (Tier 2 Unleaded)				
MOD		TEST GROUP		M	VEHICLE TYPE E-passenger car; LDT=light-duty truck; DV=medium-duty vehicle; LVW=loaded ehicle weight; ALVW=adjusted LVW)	CATEGORY vehicle: T	EMISSION STAND  (LEV=low emis LEV= transitional LEV EV; SULEV=super Ui	sion /:	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG≃compressed/ liquefled natural gas; LPG=liquefled petroleum gas}				

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

AVE				NMOG @ RAF=* CH4 RAF = *		CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram											
CER	0.056 0.085		NMOG	NMHC CERT [g/mi]	NMHC STD [g/mi]	mg=millig	ot-soak K	r (8/mı)≖ruı	nning loss 1000 miles	ORVR [	g/gallon	dispensed]	on-board r	efueling var	or recovery	g=gram	
0.05			CERT [g/mi]				[g/mi]		x [g/mi]	ŀ	HCHO [r	ng/mi]	PM [		Hwy NO		
Water on the same		@ 50K	[3,]	[8,]		CERT	STD	CERT	STI	D   C	ERT	STD	CERT	STD	CERT	STD	
	446.725		0.077	*	0.100	1.9	3.4	0.1	0.2	2	*	15	+	*	0.02	0.27	
		@ UL	0.077	*	0.130	1.9	4.2	0.1	0.3		*	18	*	•	0.02	0.40	
	@ 50	0°F & 4K	*	*	*	•	*	*	*		*	*	*	*	*	+	
@ 20	CO [g/mi] @ 20°F & 50K		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)			ox [g/mi] osite)	CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]			O [g/mi] [US06]		NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
50			SFTP 2 = @ UL (Tier 1,		CERT	STD	CERT	STD	CERT	STD	CER	T STE	CER	STD	CERT	STD	
CERT	5.5			SFTP @ 4K	*	*	*	*	0.14	0.25	2.6	10.	0.20	0.27	0.7	3.5	
STD	12.5			SFTP @ UL	0.21	1.04	*	*	*	•	9.0	14.6	3 *	<del>  .</del>	1.8	4.9	
@ UL			ATIVE FA	MILY 1	EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				E	EVAPORATIVE FAMILY 4			
	3-D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVE		2-D	RL	ORVR	
CERT	0.9	0.7	0.00	1 0.08	0.51	0.44	0.000	0.12	*	*	*	*		+	*	*	
STD	2.0	2.5	0.05	0.20	0.65	0.85	0.05	0.20	*	*	•	+	-	*	*	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

**BE IT FURTHER RESOLVED:** That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order. This Executive Order hereby supersedes Executive Order A-009-0622 dated January 27, 2003.

Executed at El Monte, California on this \_\_\_\_\_\_/8<sup>-29</sup>\_ day of July 2003.

Allen Lyons, Chief

Mobile Source Operations Division