

DAIMLERCHRYSLER CORPORATION

EXECUTIVE ORDER A-009-0635 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP			VEHICLE TYPE (PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)			STAND (LEV=low er transitional	UST EMISSION ARD CATEGORY nission vehicle; TLEV LEV; ULEV=ultra LEV V=super ULEV)		EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefled natural gas; LPG=liquefled petroleum gas)			
			XT04.75J(,	МС	V: 3,751 ~ 5,750 pounds ALVW 1) USEPA Bin 8a (Opt) 2) Counted as ARB LEV I SULEY				EV	EXH: 120K EVAF1&3: 120K EVAF2&4/ORVR: 150K/120K	Gasoline (Tier 2 Unleaded)			
No.		APORA Vily (e		No) .	SPECIAL FEAT EMISSION CONTROL				OC/TWC=oxidizing/3-way cat. WU= warm-up cat. O2S/HO2S	ADSTWC=adsorbing TWC				
1	4CR	XE010	1GDH	1		2TWC, 2	HO2S(2), SFI, OBD (F	9	AFS/HAFS=air-fuel ratio sensor/heated AFS_EGR=exhaust					
2	4CR	CRXR0218GDH					*	·- ·- ·- ·- ·- ·- ·- ·- ·- ·- ·- ·- ·- ·		gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger					
3	4CR	RXE0130GDH					*								
4	4CR	XR028	XR0283GEH				CAC=charge air cooler OBD (diagnostic prefix 2=parailei	F) / (P)=full /partial on-board (2) suffix=series							
EVAI No.		ECS No.	ENGINE SIZE (L			VEHICLE VEHICLES SUBJECT TO SFTP MAKES & MODELS STANDARDS ARE UNDERLINED ABBREVIATIONS:									
1		1	4.7			Dodge Dakota Pickup 2WD/4WD									
2		1	4.7		Dodge Ram 1500 Pickup 2WD/4WD										
3		1	4.7		Dodge Durango 2WD/4WD										
4		1	4.7	Dodge Ram 1500 Pickup 2WD/4WD											

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]) RAF= * AF = *	NMOG or	CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day dlurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refuelling vapor recovery g=gram											
CER			NMOG NMHC		NMHC	mg=millig	ot-soak K	ւ լց/mւյ≃ru	nning lo: 1000 mile	SS ORV	R [g/gallo	n dispensed] 'ahrenheit	on-board re= SFTP=supp	fueling vap	or recovery	g=gram	
•			CERT [g/mi]	CERT	[g/mi]		CO [g/mi]		NOx [g/mi]			[mg/mi]	PM [g/mi]		Hwy NOx [g/mi]		
***************	Soliving to consequence		[9/111]	[g/mi]	101	CERT	STD	CER.	T S	TD	CERT	STD	CERT	STD	CERT	STD	
			0.074	*	0.125	1.7	3.4	0.07	0	.14	*	15		*	0.02	0.19	
257		@ UL	0.074	*	0.156	1.7	4.2	0.07	0	.20	*	18	•	*	0.02	0.27	
	@ 50°	F & 4K	*	•	*	•	*	*		•	*	*	*	*	*	*	
	CO [g/mi] @ 20°F & 50K		SFTP 1 = @ 4K (SULEV, U LEV) or 50K (Tier 1, SFTP 2 = @ UL (Tier 1, Ti		, ULEV, NMHC+NC				NMHC+NOx [g/mi] [US06]		CO [g/mi] [US061		NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC031		
50					CERT	STD	CERT	STD	CER1	ST	D CE	RT STI			CERT	STD	
CERT	5.0	100	SFTP	@ 4K	*	•	*	*	0.08	0.4	10 1	.6 10.	5 0.05	0.31	0.6	3.5	
STD	12.5		SFTP	@ 120K	0.11	1.06	*	*	*	*	3	.7 16.	9 *		1.3	5.6	
@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2				EV	APORA	TIVE F	MILY 3	Ε\	EVAPORATIVE FAMILY 4			
	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RI	- ORV		2-D	RL	ORVR	
CERT	1.3	1.0		*	0.58	0.46	0.000	0.07	0.7	0.5	0.0	00 *	0.40	0.33	0.000	0.04	
STD	2.0	2.5	0.05	*	0.90	1.15	0.05	0.20	2.0	2.5	0.0	5 *	0.90	1.15	0.05	0.20	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of July 2003.

Allen Lyons, Chief

Mobile Source Operations Division