## DAIMLERCHRYSLER CORPORATION

EXECUTIVE ORDER A-009-0651 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR TEST GROU			GROU	•	MD\	VEHICLE TYPE passenger car; LDT=light-dut /=medium-duty vehicle; LVW= hicle weight; ALVW=adjusted	loaded	STAND (LEV=low of transitions	AUST EMISSION DARD CATEGORY emission vehicle; TLE II LEV; ULEV=ultra LE EV=super ULEV)	V=	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)  FUEL TYPE (CNG/LNG=compre liquefied natural g LPG=liquefied petro gas)					
200	4	4CRXT05.75J0			ME	V: 3,751 – 5,750 pounds A		Bin 8a (Opt) as ARB LEV I SUL	.EV	EXH: 120K EVAF3: 120K EVAF1&2/ORVR: (Tier 2 Unleaded 150K/120K						
No.		PORA ILY (E		No	0.	SPECIAL FEAT EMISSION CONTROL			e	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S						
1	4CRX	4CRXR0283GEH				2TWC, 2H	O2S(2), S	SFI, EGR, OB		AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFUSFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
2	4CRX	4CRXR0218GDH					*									
3	4CRX	4CRXE0130GDH					*									
4		•														
EVAI No.		CS lo.	ENGINE SIZE (L)			VEHICLE MAKES & MODELS		HICLES SUB.	AB	ABBREVIATIONS:						
1	1 5.7							Dodge Ram 1500 Pickup 2WD/4WD								
2	1 5.7 Dodge Ram 1500 Pickup								2WD	WD/4WD						
3	3 1 5.7			T		Dodge Durango 2WD/4WD										
*		* *														

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	OG FL RAGE		NMOG @ RAF= * CH4 RAF = *			NMOG or	nitrogen	HCHO=fo	rmaldehyde	PM=pai	rticulate	matter	CH4 hydroca RAF=reacti	vity adjustm	ent factor	2/3 D [g/test	]=2/3 day	
CER	CERT STD		NMC		NMHC CERT [g/mi]	NMHC STD [g/mi] 0.125 0.156	mg=milli	gram mi	=mile K=1	1000 miles	F=d	degrees l	n dispensed Fahrenheit		erueling vap plemental fe			
		•					CO [g/mi]		NOx [g/mi]			HCHO [mg/mi]		PM [	g/mi]	i] Hwy NOx [g/mi]		
				ni]			0.9 0.9	3.4 4.2	CERT	r ST	D	CERT	STD	CERT	STD *	0.01 0.01	0.19 0.27	
	@ 50K		0.07	76					0.06	0.1	4		15	•				
		@ UL	0.076						0.06	0.2	0	*	18					
	@ 50	°F & 4K	*					•	•			•		•		•	*	
CO [ @ 20		SFTP 1	SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)			NMHC+NOx [g/mi] (composite) (			CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]	NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
	50K		SFTP 2 = @ UL (Tier 1		TLEV)	CERT	STD	CERT	STD	CERT	STE	CE	RT ST	D CER	T STD	CERT	STD	
CERT	6.4		, d ( )	SFTP @	0 4K	•				0.05	0.40	0 5	i.0 10.	5 0.04	0.31	0.2	3.5	
STD	12.5			SFTP @	120K	0.10	1.06		•			11	0.9 16.	9 *		0.2	5.6	
@ UL	EVAPORATIVE FAMILY 1					EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				E	EVAPORATIVE FAMILY 4			
W OL	3-D	2-0	)	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	R	L ORV	R 3-D	2-D	RL	ORVR	
CERT	0.40	0.3	3 (	0.000	0.04	0.58	0.46	0.000	0.07	0.7	0.5	0.0	00 *	•		*	*	
STD	0.90	1.1	5	0.05	0.20	0.90	1.15	0.05	0.20	2.0	2.5	0.0	5 *		*	*	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_\_ day of July 2003.

Allen Lyons, Chief

Mobile Source Operations Division