	 , cany		Dana			ORECTRON	і Аделі	<b>7</b>	
	 			-		-	-	-	
-		нн	IES S	( )I	IR	1.65	5 R(	٦A	RD
-	<b></b>			~					

DAIMLERCHRYSLER CORPORATION

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL TEST GROUP			P	VEHICLE (PC=passenger car; LI MDV≕medium-duty ve vehicle weight; ALV	DT=light-duty tru hicle; LVW=load	ded	CATEGOR	EMISSION STAND Y (LEV=low emis 'LEV= transitional LEV LEV; SULEV=super U	ision /:	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefled natural gas; LPG=liquefled petroleum gas)					
2004 4CRXV02.4VH0			10	PC			1) USEPA Bin 8 2) Counted as ARB LEV I ULEV			EXH/ORVR: 100K EVAF1: 100K EVAF2:150K	Gasoline (Tier 2 Unleaded)					
No.		APORA AILY (E		N		CIAL FEATUR		* = not applicable		OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing WU= warm-up cat. O2S/HO2S=oxygen sensor/heated						
1	4CR	CRXR0101GBA				TWC, SFI, T	С, НО	2S(2), OBD (	_ ∦AF	AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust						
2	4CR	XR010	1GBB	2		*						gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI				
3		*		3			*		TB	TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=fuli /partial on-board						
4		*		4			*		dia	ignostic prefix 2=parallel	(2) suffix=series					
EVAI No.		ECS No.	ENGIN SIZE (I		VEHICLE MAKES & MO				ECT TO SFTP	ABBI	BREVIATIONS:					
1		1	2.4					T-4/SX 2.0								
2		1	2.4	T				Chrysler PT Cruiser								
*		*	*		<i></i>	*										
*		* *							*	· · · · · ·						

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NM	OG FL	FFT	NMOO	6 @ RAF= *		CH4=met	hane NMO	Ganon CH	4 organia a			. husterer:				
AVERAGE [g/mi] CH4 RAF = *				NMOG or	CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diumal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram											
CER	T	STD	NMOG		NMHC STD	diumai+i mg≃milli	gram mi=	L[g/mi]≕ru =mile K=	inning loss 1000 miles	ORVR[( F≖de	g/gallon di grees Fah	ispensed] renheit	=on-board r SFTP=sup	efueling vap plemental fe	or recovery deral test p	g=gram
0.04	8 0	0.053	CERT [g/mi]	CERT [g/mi]	[g/mi]		) [g/mi]		Ox [g/mi]		ICHO (m		PM [	g/mi]	Hwy NC	x [g/mi]
······································						CERT	STD	CER	T ST		ÉRT	STD	CERT	STD	CERT	STD
		@ 50K 0.075 *		*	0.100	1.3	3.4	0.08	0.1	4	*	15	*	*	0.04	0.19
		@ UL	0.075	*	0.125	1.3	4.2	0.08	0.2	0	*	18	*	*	0.04	0.27
	@ 50	°F & 4K	•	*	*		*	*	+		•	*	*	*	*	*
CO [ @ 20	g/mi] °F &	🐘 ` LE	:v) or 50K	ULEV, ULEV, (Tier 1, TLEV)	NMHC+N (comp			[g/mi] posite)		C+NOx [US06]		) [g/mi] US06]		HC+NOx		[g/mi] C031
50	К	SFTP 2	= @ UL (T	ier 1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CER	r   STI			CERT	STD
CERT	3.2			SFTP @4K	*	*	*	*	0.01	0.14	2.4	8.0	0.04	0.20	0.2	2.7
STD	10.0			SFTP @ UL	0.11	0.71	+	*	*	*	9.3	11.	1 *	*	1.1	3.7
@ UL	DUI EVAPORATIVE FAMILY 1					PORATIV	E FAMIL	Y 2	EVA	PORATI	VE FAM	ILY 3	E	VAPORAT	IVE FAMI	LY 4
	3-D	2-0		L ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVI	R 3-D	2-D	RL	ORVR
CERT	0.8	1.3	0.0	01 0.06	0.46	0.49	0.000	0.13	*	*	*	•	*	*	*	*
STD	2.0	2.5	5 0.0	05 0.20	0.50	0.65	0.05	0.20	*	*	+	*	*	*	+	*

**BE IT FURTHER RESOLVED:** That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

**BE IT FURTHER RESOLVED:** That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order. This Executive Order hereby supersedes Executive Order A-009-0649 dated June 16, 2003.

Executed at El Monte, California on this  $Z^{\nu D}$ 

day of October 2003.

Allen Lyons, Chief Mobile Source Operations Division