

TOYOTA MOTOR CORPORATION

EXECUTIVE ORDER A-014-0473 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP			MI	VEHICLE TYPE C=passenger car; LDT=light-duty truck: DV=medlum-duty vehicle; LVW=loaded ehicle weight; ALVW=adjusted LVW)	CATEGOR' vehicle; 1	EMISSION STANDAY (LEV=low emis LEV= transitional LEV LEV; SULEV=super UL	sion /:	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)			
200		4TYXV02.4MXA				PC	L	EV II SULEV		150K / 150K	Gasoline			
No.		APORA VILY (E		*	No.	SPECIAL FEATURES EMISSION CONTROL SYST		* = not applicable	OC	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TO WU= warm-up cat. O2S/HO2S=oxygen sensor/heated (
1	4TY	YXR0135A41			1	WU-TWC, TWC, HAFS		AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air Injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler DOR=direct O3 reduction OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
2		*			2		*							
3		*			3		*							
EVAF No.		ECS No.	VEI					ECT TO SFTP E UNDERLINED	ABBREVIATIONS:					
1	L_	1 2.4 Toyota: Camry												

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bidual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET NMOG @ RAF = * AVERAGE [g/mi] CH4 RAF = *					NMOG or	CH4=met	hane NMO	G=non-CH	4 organic	gases	NMHC=n	on-CH4 hydro	carbone CC		anaulda MZ		
	CERT STD		CH4 RAF = * NMOG NMHC		NMHC	nitrogen dlurnai+h mg≂millig	ot-soak	RL [g/mi]≕i	a ⊾w=r	ss O	ate matte RVR [g/g	r KA⊁≕reac allon dispense	tivity adjustr ad]≃on-board	ment factor d refueling v	2/3 D [g/te apor recove	est]≖2/3 day	
0.04	2	0.053	CERT [g/mi]	CERT [g/mi]	STD [g/mi]	CO [g/mi]		NOx [g/mi]			F=degrees Fahrenheit HCHO [mg/mi]		PM [g/mi]		l federal test procedure Hwy NOx [g/mi]		
	@ 50K		*	*	•	*	*	· CER	*		CERT STD		CERT	STD	CERT	STD	
144	@ UL		0.004	•	0.010	0.1	1.0	0.01	0.0	0.02 0.1		4	•		0.01	0.03	
射学療	@ 50°F & 41		*	*	*	*	*	*	*		*	*	*	*	*	*	
CO [@ 20	°F&	LE	V) or 50K	ULEV, ULEV, (Tier 1, TLEV)					NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]	NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]			
	50K		SFTP 2 = @ UL (1		CERT	STD	CERT	STD	CERT	S	TD C	ERT STI			CERT	STD	
CERT	1.3		166	SFTP 1	*	*	*	*	0.003	0.	14	3.8 8.0	0.01	0.20	0.1	2.7	
STD	10.0	17		SFTP 2	*	*	*	*		١.	.	* *	*	*	*	*	
@ UL		VAPORA			EVAPORATIVE FAMILY 2				EV	APOR	ATIVE F	AMILY 3		EVAPORATIVE FAMILY 4			
	3-D	12-D			3-D	2-D	RL	ORVR	3-D	2-0) F	RL ORVI		2-D	RL	ORVR	
CERT	0.23	0.20			*	*	*	•	*	*		* *	*	+	•	*	
STD	0.35	0.3	5 0.0	5 0.20		*	*	*	*	*		* *	- 	+	*	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are permitted intermediate in-use compliance standards pursuant to 13 CCR Section 1961(a)(10).

BE IT FURTHER RESOLVED: That the manufacturer has requested that the listed vehicles be conditionally certified as a partial zero emission vehicle (PZEV) and determined to qualify for a baseline PZEV allowance of 0.2 under the amendments to 13 CCR Section 1962(c) that were referenced in the Air Resources Board's Resolution 03-04 adopted by the Board on April 24, 2003 (part of the 2003 Zero Emission Vehicle (ZEV) Amendments). This determination for PZEV qualification is conditional on these amendments being adopted by the Executive Officer and approved by the Office of Administrative Law (OAL), after which they will become effective.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 29th day of July 2003.

Allen Lyons, Chief Mobile Source Operations Division