California Environmental Protection Agency	KIA MOTORS CORPORATION	EXECUTIVE ORDER A-315-0041 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles
		and medium-buty venicles

Jugar

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR TEST GROUP 2004 4KMXT03.5G02				_	VEHICLE TYPE (PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW) LDT: 3,751-5,750 Pounds LVW	STANDA (LEV=low en transitional SULE 1) USEPA Bi	JST EMISSION ARD CATEGORY hission vehicle; TLEV: LEV; ULEV=uitra LEV V=super ULEV) n 9 s ARB LEV I ULEV						
No.	EVAPORATIVE FAMILY (EVAF) 4KMXR0160G02				No.	SPECIAL FEATURE EMISSION CONTROL SYS	TEMS (ECS)	BWU= warm-up cat. O2S/H	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/puised AIR MFI/SFI= multiport fuel injection/sequential MFI				
2	*				2	2HO2S(2), 2WUTV	*						
3		*					*	TBI= throttle body injection TC/SC=turbo /super charger					
4					4		*	diagnostic prefix 2=para	illei (2) suffix=series				
EVAI No.		ECS No.	ENGI SIZE				/EHICLES SUBJ TANDARDS AR	ECT TO SFTP E UNDERLINED	ABBREVIATIONS:				
1		1 3.5 Kia Sorento 2WI							/D				
			· · · · · ·										

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET NMOG @ RAF=* AVERAGE [g/mi] CH4 RAF = *				NMOG or	Interogen	HUHUSTOP	maldehvde	PM=part	ticulate m	natter F	2AF=reactiv	rbon CO=c vity adjustme	ant factor	2/3 D (a/teast	1-2/2 day
CER	Т	STD	NMOG	NMHC		diurnal+ho mg=millig	x-soak RL	- [g/mi]≖run	ning loss 000 miles	ORVR [g/gallon	dispensed] hrenheit	=on-board n SFTP=supp	efueling var	or recovery	a≖aram
0.05	o	0.085	CERT CERT [g/mi] [g/mi]		[g/mi]		[g/mi]			- F	HCHO [mg/mi]		PM [g/mi]		Hwy NO	
1204			[9,111]	[3,]		CERT	STD	CERT	STC) (C	ERT	STD	CERT	STD	CERT	STD
		@ 50K	0.054	*	0.075	0.5	3.4	0.1	0.2		1	15	*	•	0.02	0.27
19100		@ UL	0.062	*	0.090	0.6	4.2	0.1	0.3		1	18	*	*	0.02	0.40
	@ 50	°F & 4K	*	*	*	*	*	*	*		•	*	*	*	*	*
@ 20	@ 20°F & 📲		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)				CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06				NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
50	ĸ	SFTP 2 =	@ UL (Tie	r 1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CEF	T STI	D CERT	STD	CERT	STD
CERT	7.5	46.5	. S	SFTP @ 4K	*	*	*	•	0.03	0.25	7.4	10.	5 0.10	0.27	0.2	3.5
STD	12.5		See. S	FTP @ UL	0.15	1.03	3.11	5.04	*	*	*	•	*	*	- *	+
		VAPORA	TIVE FAI	MILY 1	EVAPORATIVE FAMILY 2 EVA				PORATI	VE FA	WILY 3	Ε'	EVAPORATIVE FAMILY 4			
_	3-D	2-D	RL	ORVR	3-D	2-D	RL.	ORVR	3-D	2-D	RL	ORV	R 3-D	2-D	RL	ORVR
CERT	1.2	1.3	0.04	0.01	*	*	*	*	*	*		*	*	*	*	*
STD	2.0	2.5	0.05	0.20	*	*	*	*	*	*	*	+	*	*	*	*

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 272 day of August 2003.

Repart Support

Mobile Source Operations Division