## **JAGUAR CARS LIMITED**

EXECUTIVE ORDER A-220-0078
New Passenger Cars, Light-Duty Trucks
and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003:

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD! YEA		TEST GROUP			VEHICLE TYPE (PC=passenger car; LDT=light-duty tru MDV=medium-duty vehicle; LVW=load vehicle weight; ALVW=adjusted LVW	ick; STAND ied (LEV=low e transitiona	UST EMISSION ARD CATEGORY mission vehicle; TLEV= I LEV; ULEV=ultra LEV; EV=super ULEV)	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200	4				PC		LEV II LEV	120K: EXH 100K: EVAF/ORVR	Gasoline				
No.		PORA IILY (E		No	SPECIAL FEATUR EMISSION CONTROL SY		* = not applicable	OC/TWC=oxidizing/3-way o	eat. ADSTWC=adsorbing TWC D2S=oxygen sensor/heated O2S				
1	4JCXR0160P1X			.1	2HAFS, 2TWC, 2I	HO2S, EGR, SFI,	AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/puised AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo/super charger CAC=charge air cooler OBD (F) / (P)=fuil /partial on-board						
2		•				. •							
3		*				*							
4		*				*	diagnostic prefix 2=parallel (2) suffix=series						
EVAI No.		CS No.				SJECT TO SFTP	ABBREVIATIONS:						
1		1 4.2			Jaguar: S-type 4.2 litre, XJ8, Vanden Plas								
•		*	•				•						
*		* *			•								
*	*   *												

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET NMOG @ RAF= * AVERAGE [g/mi] CH4 RAF = *			NMOG or	nitrogen	HCHO=for	rmaldehyde	PM≖pari	ticulate ma	tter R/	\F≐reactiv	bon CO=c	ent factor	2/3 D [g/test	]=2/3 day		
CER	.     1		NMOG NMHC		NMHC	mg=millig		∟(g/mij=ru =mile K=1	inning loss 1000 miles	OKVK [g/ F≃degi	gallon d rees Fah		on-board re SFTP=supp			
0.07	0.075 0.053		CERT		[g/mi]		[g/mi]		x [g/mi]		CHO [m		PM [g		Hwy NO	
W-9000 - 11 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1			[g/ml]			CERT	STD	CER	r ste	CE	RT	STD	CERT	STD	CERT	STD
		@ 50K	0.044	*	0.075	0.3	3.4	0.02	0.0	5 0.	4	15	•	•	0.01	0.07
		@ UL	0.049	*	0.090	0.3	4.2	0.02	0.07	7 0.	4	18	•	•	0.01	0.09
	@ 50°	F & 4K	0.136	*	0.150	0.6	3.4	0.02	0.0	5 1	ī	30	•	*		
	CO [g/mi]   SFTP 1 = @ 20°F & LEV			= @ 4K (SULEV, ULEV, EV) or 50K (Tier 1, TLEV)		NMHC+NOx [g/mi] CO [g/ (composite) (compo			NMHC+NOx [g/mi] [US06]			) [g/mi] US06]		HC+NOx ij [SC03]		[g/mi] C03]
50		SFTP 2 =	@ UL (Tier	1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CER	T STE	CERT	STD	CERT	STD
CERT	3.3		**************************************	SFTP 1	<b>*</b> .	*	*	•	0.09	0.14	0.6	8.0	0.01	0.20	0.1	2.7
STD	10.0			SFTP 2	. •	*	*	*	*	*	•	•			•	•
@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2 EVAP				APORATIVE FAMILY 3			E'	EVAPORATIVE FAMILY 4			
	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVE	₹ 3-D	2-D	RL	ORVR
CERT	1.1	1.1	0.005	0.002	*	*	*	*	•	*	*	•	•	•	•	•
STD	2.0	2.5	0.05	0.20	*	•	*	*	•	*	*	•	•	•	*	*

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 1274 day of March 2003.

Allen Lyons, Chief

Mobile Source Operations Division