EXECUTIVE ORDER A-023-0364 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2, and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP			MD'	VEHICLE TYPE =passenger car; LDT=light-duty truck V=medium-duty vehicle; LVW=loaded shicle weight; ALVW=adjusted LVW)	CATEG	EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV)			EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefled natural gas; LPG=liquefled petroleum gas)			
200		4HNXV01.35A6				PC		ULEV			100K / 100K	Gasoline plus Battery-Assist			
No.		EVAPORATIVE FAMILY (EVAF)			о.	SPECIAL FEATURES EMISSION CONTROL SYST					C/TWC=oxidizing/3-way	cat. ADSTWC=adsorbing TWC O2S=oxygen sensor/heated O2S			
1	4HNXR0099AAA				1	WUTWC, TWC, AFS, H	02S(2), EGR	₩AF	FS/HAFS=air-fuel ratio s	ensor/heated AFS EGR=exhaust					
2	*			2	2		*	— ga	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI						
3		•			3	*					TBI= throttle body injection TC/SC=turbo /super charger				
4		* 5					*	dia	CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
EVA No.		CS No.	ENGÍN SIZE (L			VEHICLE . V MAKES & MODELS S1	EHICLES SU ANDARDS	HICLES SUBJECT TO SFTP NDARDS ARE UNDERLINED		ABB	ABBREVIATIONS:				
1		1	1.3	П		Honda Civic Hybrid									
*	•			*											
*		*				•									
*	* * *								•						

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NM AVE	OG FL RAGE	EET [g/mi]	NMOG @ CH4 R		NMOG or	Inttrogen	HCHO=10	irmaidenvde	ì РМ#рап	iiculate m	natter i	Z∆Færeseti	vitu adinotm	carbon mono	2/2 D [a/4aa4	1-2/2 days	
CER	RT STD NMOG NMH		NMHC	NMHC	diurnal+he	⊃₹- 5 0&K №	ır (8/mı)=ırı	nning loss 1000 miles	ORVR [g	g/gallon	dispensed hrenheit	=on-board :	refueling var plemental fe	or recovery	g≖gram		
0.04	5	0.053	CERT [g/mi]	CERT [g/mi]	[g/mi]		[g/mi]		x [g/mi]	Н	ICHO (ı	[mg/mi]	PM [g/mi]	Hwy NO	x [g/mi]	
free transfer grown	TOWN TOWN		[8,.,,,]			CERT	STD	CERT	STE	C	ERT	STD	CERT	STD	CERT	STD	
		@ 50K	0.011	*	0.040	0.5	1.7	0.1	0.2	0	0.1	8	*	*	0.2	0.3	
		@ UL	0.016	*	0.055	0.8	2.1	0.1	0.3	C	0.2	11	*	•	0.2	0.4	
	@ 50	°F & 4K	*	*	*	*	*	*	*		•	*	*		*	*	
@ 20		E LE	= @ 4K (SUL V) or 50K (TI	er 1, TLEV)	NMHC+NOx [g/mi] (composite)		CO [g/mi] (composite)		NMHC+NO [g/mi] [US0				NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
50	50K		SFFP 2 = @ UL (Tier 1, TLEV)		CERT	STD	CERT	STD	CERT	STD	CEF	RT ST			CERT	STD	
CERT	1.8			SFTP 1	*	*	*	*	0.09	0.14	2.7	7 8.0	0.06	3 0.20	0.5	2.7	
STD	10.0			SFTP 2	*	*	•	*	+	*	*	*	*	*	•		
@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2 EV					EVAPORATIVE FAMILY 3				EVAPORATIVE FAMILY 4			
3 02	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORV	R 3-D	2-D	RL	ORVR	
CERT	1.1	1.3	0.01	0.10	*	*	*	*	*	*	*	+	*	+	*	*	
STD	2.0	2.5	0.05	0.20	*	*	*	*	*	*	*	*	*	*	*	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _______ day of August 2003.

RAllen Lyons, Chief

Mobile Source Operations Division