HONDA MOTOR CO., LTD.

EXECUTIVE ORDER A-023-0377 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODI		TEST GROUP			VEHICLE TYPE (PC=passenger car; LDT=light-du: MDV=medium-duty vehicle; LVW- vehicle weight; ALVW=adjusted	EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV)			EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG≃compressed/ liquefied natural gas; LPG≃liquefied petroleum gas					
2004			XV01.02/	46	PC		ULEV			100K / 100K	Gasoline plus Battery- Assist				
No.	FAMI	ILY (E	(TIVE VAF)	No	SPECIAL FEAT EMISSION CONTROL	URES & Systems	(ECS)	* = not applicable	OC/	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing WU= warm-up cat. O2S/HO2S=oxygen sensor/heate					
1	4HNX	(R008	3AAA	1	TWC, WUTWC, AF	S, EGR, H	102S(2), SF	MAPS	/MAFS≔air-fuel ratio se	nsor/heated AFS_FGR=exhause					
2		* 2				*		gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series							
3		* 3				*									
4						*									
EVAF No.		CS lo.	ENGINE SIZE (L)		VEHICLE MAKES & MODELS		LES SUBJE ARDS ARE	ABBREVIATIONS:							
1		1	1.0		Honda Insight (Manual Transmission)										
*	* *														
*		*	*												
*	* *		*			•									

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	OG FL RAGE		NMOG @ RAF=* CH4 RAF = *		NMOG or NMHC								rbon CO=c			
CER	T	STD	NMOG	3 THIN 10		mg=millig	Je-avan ili	- [g/mm]−ru	nning loss 1000 miles	SURVE	(g/gallol	n dispensed) ahrenheit	=on-board r SFTP=supp	efueling var	or recovery	α=gram
0.04	5	0.053	CERT [g/mi]	CERT [g/mi]	STD [g/mi]		[g/mi]	NO	Ox [g/mi]		HCHO [r	[mg/mi]	PM [c	g/mi]		x [g/mi]
e de la companya de	000 Q 200 V V V V	-				CERT	STD	CER	T ST	D (CERT	STD	CERT	STD	CERT	STD
		@ 50K	0.023		0.040	0.3	1.7	0.03	0.	2	*	8	*	*	0.1	0.3
	sado e e	@ UL	0.029	* *	0.055	0.6	2.1	0.03	0.	3	*	11	*	*	0.1	0.4
	@ 50	°F & 4K	*	*	*	*	*	*	*		*	*	*	*	*	*
@ 20		LE LE	= @ 4K (SUL V) or 50K (T		site)	CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]			CO [g/mi] [US06]	NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
50	N.	OLIL Z	@ UL (Tier	1, (LEV)	CERT	STD	CERT	STD	CERT	STD	CE	RT ST	D CER1	STD	CERT	STD
CERT	0.9			SFTP 1	*	.*	*	*	0.02	0.14	1 1.	1 8.0	0.09	0.20	0.2	2.7
STD	10.0			SFTP 2	*	*	*	*	*	*			•	*	*	*
@ UL			TIVE FAM	ILY 1	EVAPORATIVE FAMILY 2 EV				EVA	EVAPORATIVE FAMILY 3 EVAPORATIVE FAMILY 4					Y 4	
	3-D	2-D	RL	ORVR	3-D	2-D	RL.	ORVR	3-D	2-D	RL			2-D	RL	ORVR
CERT	1.4	1.6	0.01	0.06	•	*	*	•	*	*	*	*	*	*	* *	- t
STD	2.0	2.5	0.05	0.20	· ·	*		*	•	*	+ +				 	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

day of October 2003.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

Allen Lyons, Chief

Mobile Source Operations Division