EXECUTIVE ORDER A-023-0378 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP				VEHICLE TYPE (PC=passenger car; LDT=light- truck; MDV=medlum-duty vehi LVW=loaded vehicle weight ALVW=adjusted LVW)	EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV)			EXHAUST (EXH) / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefled natural gas; LPG=liquefled petroleum gas)				
200		4HNXV01.0NCE				PC	LEV II SULEV			120K: EXH 100K: EVAF/ORVR	Gasoline plus Battery- Assist				
No.		VAPORATIVE NAMILY (EVAF)			No.	SPECIAL FEAT EMISSION CONTROL			* = not applicable	0.8	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing WU= warm-up cat. O2S/HO2S=oxygen sensor/heate				
1	4HN	4HNXR0083AAA			1	TWC, WUTWC,	AFS, EG	R, HO2S, SFI,	∭ A	AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI					
2		*			2		*		- 19 A						
3		*			3	*					TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=fuil /partial on-board				
4		* 4			4		*		ď	diagnostic prefix 2=parallel (2) suffix=series					
EVA No.	F	ECS ENGINE No. SIZE (L)			VEHICLE MAKES & MODELS			CT TO SFTP UNDERLINED	ABE	ABBREVIATIONS:					
1		1 1.0				Honda Insight (CVT Transmission)									
*		• •				•									
*															
*	* *					•									

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	OG FLI RAGE [@ RAF=* RAF =**	NMOG or	CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of nltrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day dlurnal+hot-soak RL [g/ml]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram											
CERT STD			NMOG	NMHC	NMHC	mg=millig	ram mi=	∟ [g/mi]=ru :mile K=1	nning ios: 1000 mile:	F=	R [g/galloi =degr ees F	n dispensed] Fahrenheit		etueling vap piemental fe			
0.04	5 0.053		CERT	CERT	[g/mi]		[g/mi]		x [g/mi]		НСНО	[mg/mi]	PM (g/mi]	Hwy NO	x [g/mi]	
0,04			[g/mi]	[g/mi]		CERT	STD	CER	r si	STD		STD	CERT	STD	CERT	STD	
		@ 50K	*	4 .	*	*		*	1	•	*		•	*	*	*	
		@ UL	0.004	*	0.010	0.02	1.0	0.01	0.0	02	0.04	4	*	*	0.004	0.03	
	@ 50°		*		*	*	*	*	1	'	*	•	*	*	*	*	
CO [@ 20	g/mi] °F &	SFTP 1	= @ 4K (SU V) or 50K (LEV, ULEV, Fier 1, TLEV)	NMHC+NOx [g/mi] CO [g (composite) (compo				NMHC+NOx [g/mi] [US06]				HC+NOx ii] [SC03]	CO [g/mi] [SC03]			
50	K	SFTP 2	= @ UL (Tier 1, TLEV)		CERT	STD	CERT	STD	CERT	ST	TD CE	RT ST	D CER	T STD	CERT	STD	
CERT	0.2			SFTP 1	*	*	*	*	0.01	0.1	14 3	.3 8.0	0.05	0.20	0.01	2.7	
STD	10.0			SFTP 2	*	*	*	*	•	*	•	• •	*	*	*	*	
@ UL	E	VAPOR	ATIVE FA	MILY 1	EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				E	EVAPORATIVE FAMILY 4			
W OL	3-D	2-0	RL.	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RI	L ORV	R 3-D	2-D	RL	ORVR	
CERT	1.4	1.6	0.01	0.06	*	*	*	*	*	*	*	•	*	*	•	•	
STD	2.0	2.5	0.05	0.20	*	*	*	*	*	*	*	•	*	*	*	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are permitted intermediate in-use compliance standards pursuant to 13 CCR Section 1961(a)(10).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

day of October 2003.

Allen Lyons, Chief

Mobile Source Operations Division