

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR TEST GR			T GROU	Р	VEHICLE TYPE (PC=passenger car; LDT=fight-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)			CATEGOR' vehicle; T	EMISSION STAND  ( LEV=low emi LEV= transitional LE LEV; SULEV=super L	ssio: V:	" EVAPORATIVE	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)			
			XV01.83	6		PC			JSEPA Bin 8 ted as ARB ULEV		100K / 100K (EVAF 1), 100K / 150K (EVAF 2)	Gasoline (Indolene)			
No.		APORA HILY (E	ATIVE EVAF)		No.	SPECIAL FEAT EMISSION CONTROL S			* = not applicabl		OC/TWC=oxidizing/3-way	cat. ADSTWC=adsorbing TWC			
1	4AD	DXR0110234			1	TWC, HO2S(2),	, AIR, SI	I, TC, CAC, C		WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/joulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series					
2	· 4AD	XR0110236			2		*								
3		*			3		*								
4		*			4		•								
EVAI No.	-	ECS No.	ENGIN SIZE (I						ECT TO SFTP E UNDERLINED	AB	BREVIATIONS: *				
1		1	1.8				•	n							
2		1	1.8					<u></u>	etta	ta					
*	*														
*		*	*						*						

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]			NMOG @ CH4 R		NMOG or	CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day dlurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram											
CER	CERT STD		NMOG	NMHC	NMHC STD	mg=millig	ot•soak Ri ram mi≃	L[g/mi]=rui mile K=1	nning los: 1000 mile:	ORV	/R [g/gallo: =degrees f	n dispensed] 'ahrenheit	on-board r∙ SFTP≖supp	efueling vap	or recovery	g≖gram	
0.05	3 (	0.053	CERT [g/mi]	CERT [g/mi]	[g/mi]		CO [g/mi]		x [g/mi]			[mg/mi]	PM [g/mi]		Hwy NOx [g/mi]		
MANAGE TO CONTROL OF THE			[g/mi]			CERT	STD	CERT	r si	D	CERT	STD	CERT	STD	CERT	STD	
		@ 50K	0.051	*	0.100	0.8	3.4	0.01	0.	14	0.3	15	*	*	0.01	0.19	
		@ UL	0.060	*	0.125	0.9	4.2	0.01	0.2	20	0.3	18	*	*	0.01	0.27	
	@ 50°	F & 4K	*	*	*	*	*	*	*		*	*	*	*	*	*	
CO [ @ 20	g/mi] °F &				NMHC+NC (compo		ni] CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
50	K	SFTP 2	= @ UL		CERT	STD	CERT	STD	CERT	S	TD CE	RT ST			CERT	STD	
CERT	1.8			SFTP 1	•	*	*	*	0.04	0.	14 2	.5 8.0	0.01	0.20	0.2	2.7	
STD	10.0			SFTP 2	0.05	0.71	•	*	*	• •		.6 11.	1 *	1	0.3	3.7	
@ UL	Ε	VAPORA	TIVE FAM	IILY 1	EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				E'	EVAPORATIVE FAMILY 4			
	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-0	RI	- ORVI		2-D	RL	ORVR	
CERT	1.0	0.8	0.02	0.05	0.46	0.43	0.001	0.001	*	*		*	*	*	<b>+</b>	*	
\$TD	2.0	2.5	0.05	0.20	0.50	0.65	0.05	0.20	*	*	•	*	*	*	*	*	

**BE IT FURTHER RESOLVED:** That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

**BE IT FURTHER RESOLVED:** The listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incoporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 36 day of June 2003.

Allen Lyons, Chief

Mobile Source Operations Division