ROUSH INDUSTRIES INC.

EXECUTIVE ORDER A-344-0004 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA	R	TEST GROUP		_	VEHICLE TYPE (PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle welght; ALVW=adjusted LVW)			EXHAUST EMISSION STANDAR CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV 1) USEPA Bin 8			EXH & ORVR / EVAP. USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG≃compressed/ liquefied natural gas; LPG=liquefied petroleum gas)			
			PORATIVE .			2) Counted as ARB					100K / 100K	Gasoline (Tier 2 Unleaded)			
No.		ILY (E		N) .	SPECIAL FEATURES EMISSION CONTROL SYSTI	& EMS (ECS)		* = not applicable	OC	/TWC=oxidizing/3-way	cat. ADSTWC=adsorbing TWC			
1	4RII	RIIR0115BAE				2TWC(2), 2HO2S(2), EG		₩Ar.	S/HAFS=air-fuel ratio s	O2S=oxygen sensor/heated O2S ensor/heated AFS EGR=exhaust					
2		•			: ["		*	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo/super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series							
3		*					*								
4		*				-	*								
EVAI No.		CS No.	ENGIN SIZE (L			VEHICLE VE	HICLES SU	JBJEC ARE L	T TO SFTP JNDERLINED	19					
1		1 4.6				Roush Stage 3 Mustang Coupe/Conv.									
*		*	*												
*		*	*				***************************************	*							
*		*	*												

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bidual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NM AVE	OG FLE RAGE [ET g/mi]		@ RAF=* RAF = *	NMOG or	Introdau		maigenvge	e PM=nai	rticulata i	matter	RAFEreschi	ity adluet y	arbon mono	2/2 D fa/4aa4	1-2/2 days	
CER	ERT STD		NMOG	NMHC CERT [g/mi]	NMHC STD [g/mi]	mg=millig	Negoak K	_ (g/mij≖rui	nning loss 1000 miles	UKVK	[g/gailon	dispensed] ahrenheit	=on-board i	refueling var plemental fe	or recovery	α=αram	
0.04	0.075		CERT [g/mi]				[g/mi]		x [g/mi]		НСНО			g/mi]		x [g/mi]	
200-1002 YVE(50'Y)	Decre grantenage ([8,]	[8,]		CERT	3.4 0.06	CERT	「 ST		CERT	STD	CERT	STD	CERT	STD	
C _p		@ 50K	0.080	*	0.100	0.5		0.1	4	*	15	*	•	0.02	0.19		
Parane	and Marines	@ UL	0.087	*	0.125	0.8	4.2	0.07	0.2	0	*	18	*	*	0.04	0.27	
	@ 50°1	F & 4K	*		•	*	*	*	*		*	*	•	*	*	*	
@ 20	°F& 🛛	SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)			NMHC+NC (compo		CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]				NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
50	K	SFTP 2 = @ UL (Tier 1		1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CE	RT ST	CER	T STD	CERT	STD	
CERT	1.5			SFTP@4K	*	*	*	*	0.11	0.14	0.	4 8.0	0.06	0.20	0.2	2.7	
STD	10.0	16.2		SFTP@UL	0.14	0.71	*	*	*	*	0.	6 11.	1 *	*	0.4	3.7	
@ UL	E/	/APORA	TIVE FAI	/ILY 1	EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				E	EVAPORATIVE FAMILY 4			
	3-D	2-D	RL	ORVR	3-D	2-D	RL.	ORVR	3-D	2-D	RL	ORV	₹ 3-D	2-D	RL	ORVR	
CERT	1.1	1.4	0.02	0.08	*	*	*	*	*	*	*	*	*	*	*	*	
STD	2.0	2.5	0.05	0.20	*	*	*	*	•	*	-	*	+	•	+	•	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ZZVD day of October 2003.

Allen Yons, Chief
Mobile Source Operations Division