

GENERAL MOTORS CORPORATION

EXECUTIVE ORDER A-006-1232 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

*													
*		+ + +		_	GMC: C15 Sierra Hybrid 2WD, K15 Sierra Hybrid 4WD								
1		1 5.3			GMC C16 Storm Muhair 2MD, K15 Silverado Hybrid 4WD								
1		1	5.3		Chevrolet; C15 Silverado Hybrid 2WD, K15 Silverado Hybrid 4WD								
EVAF No.		ECS ENGINE VEHICLE No. SIZE (L) MAKES & MO			HICLES SUB.	JECT TO SFTP	ABBREVIATIONS:						
4	•	*					CAC≖charge air cooler OBC diagnostic prefix 2=parallel) (F) / (P)≂full /partial on-hoar					
3		*			*		gas recirculation AIR/PAIR=secondary air injection/pulse AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-boar						
2		*			1	· · · · · · · · · · · · · · · · · · ·							
1	5GN	5GMXR0176820			2TWC, 2HO2S(2		WU= warm-up cat. O2S/HO2 AFS/HAFS=air-fuel ratio sens	tor/heated AES ECDmaybe					
No.	FAI	APORA VILY (E	VAF)	No	SPECIAL FEATURES EMISSION CONTROL SYSTE	& MS (ECS)	* = not applicable	OC/TWC=oxidizing/3-way car	t. ADSTWC=adsorbing TW(
200		5GMXT05.3178			MDV: 3751 - 5750 Pounds ALVW		USEPA Bin 8a ted as ARB SULEV	EXH/ORVR: 120K EVAF: 150K	Gasoline plus Battery-Assist				
MOD YEA		TEST GROUP			VEHICLE TYPE (PC=passenger car; LDT=iight-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; GVW=gross VW)	STAN (LEV=low transition	IAUST EMISSION DARD CATEGORY emission vehicle; TLEV al LEV; ULEV≖ultra LEV ILEV≖super ULEV)	EXHAUST (EXH) / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefled natural gas; LPG=liquefled petroleum gas)				

The exhaust and evaporative emission standards (STD), as requested by the manufacturer, and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	OG F			0 RAF=* AF = *	NMOG or							H4 hydroca RAF≖reactiv				
CER	T	STD	NMOG	NMHC	INMING	diurnai+ho mg≃milligi		e (aum)_un	nning loss 000 miles	UKYK	(g/ganor	ı aispenseaj	≖on-board r	efueling var	or recovery	/ g≖oram
			CERT [g/mi]	CERT [g/mi]	STD [g/mi]	CO	[g/mi]	NO	x [g/mi]		HCHO	ahrenheit [mg/mi]	PM [plemental fe g/mi]		rocedure x [g/mi]
	Segrana.					CERT	STD	CERT	ST	D C	ERT	STD	CERT	STD	CERT	STD
		@ 50K	0.055	*	0.125	1.0	3.4	0.09	0.1	4	*	15	*	*	0.03	0.19
Ĺ		@ UL	0.066	*	0.156	1.3	4.2	0.12	0.2	0	•	18	*	•	0.07	0.27
4	@ 5	0°F & 4K	*	*	*	*	*	*	•		•	•		*	*	*
@ 20	*F&	M LEV	@ 4K (SULE) or 50K (Tie	r 1, TLEV)	NMHC+NC (compo	x [g/mi] osite)		g/mi] oosite)		C+NOx (US06)		CO [g/mi] [US06]		HC+NOx		[g/mi] C031
50	K	SFTP 2 =	@ UL (Tier 1	I, TLEV)	CERT	STD	CERT	STD	CERT	STD	CE				CERT	STD
CERT	3.6		SF	TP @ 4K	*	*	*	*	0.1	0.4	1.	8 10.5		+	0.4	3.5
STD	12.5		SF	TP @ UL	0.15	1.06	*	•	*		2.			*	0.9	5.6
@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2 EVAPOR					PORAT				VAPORATIVE FAMILY 4		
	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL			2-D	RL	ORVR
CERT	0.61	0.67	0.00	0.14	*	*	•	*	*		+ ::-	*	3-0	2-0	T.	URVR *
STD	0.90	1.15	0.05	0.20		*	*	 		*	+ +	+			-	-

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 2304 day of June 2004.

Allen Lyons, Chief Mobile Source Operations Division ons, Chief