

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD! YEA		TEST GROUP		VEHICLE TYPE (PC=passenger car; LDT=ilght-duty truck; MDV=medlum-duty vehicle; LVW=loaded vehicle weight; GVW≃gross VW)	STAND (LEV=low of transitions	AUST EMISSION DARD CATEGORY Emission vehicle; TLEV: ILEV; ULEV=ultra LEV; EV=super ULEV)		FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200	5 50	5GMXT06.0198		MDV: 5751 - 8500 Pounds ALVW	1 -	SEPA Bin 10a ted as ARB ULEV	EXH: 120K EVAF/ORVR: 120K	Dual-Fueled: Gasoline (Tier 2 Unleaded) or CNG				
No.		ORATIVE Y (EVAF)	No	SPECIAL FEATURES & EMISSION CONTROL SYSTEM		* = not applicable	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S					
1	5GMXR0223860			2WUTWC, 2TWC, 2HO	2S(2), SFI, C	AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed						
2	5GMXF	5GMXR0223861		*		AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo/super charger [CAC=charge air cooler OBD (F) / (P)=full /partial on-board						
3		*		*								
4		•			diagnostic prefix 2=parallel (2) suffix=ser							
EVAI No.	F EC					ECT TO SFTP E UNDERLINED	ABBREVIATIONS:					
1	1	6.0		Chevrole	t: C2500 HD	00 HD Silverado 4WD						
1	1	6.0		GN	AC: C2500 H	HD Sierra 4WD						
2	1 6.0			Chevrolet: C2500 HD Silverado 2WD, K2500 HD Silverado 4WD								
2	1	6.0		GMC: C2500 HD Sierra 2WD, K2500 HD Sierra 4WD								

The exhaust and evaporative emission standards (STD), as requested by the manufacturer, and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET NMOG @ R AVERAGE [g/mi] CH4 RAF		) RAF=* AF = *	NMOG or	nitrogen	<b>HCHO</b> ≃for	maldehyde	PM=part	ticulat	te matter	RAF=reactive	ity adjustm	arbon mono ent factor 2	2/3 D [g/test	]=2/3 day	
CER	т :	STD NMOG NMHC		NMHC	diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram mg=milligram mi=mile K=1000 miles F=degrees Fahrenheit SFTP=supplemental federal test procedure									ocedure		
*	*	*	CERT [g/mi]	CERT [g/mi]	[g/mi]		[g/mi]		x [g/mi]	_	нсно		] Mq		Hwy NO	
						CERT	STD	CERT			CERT	STD	CERT	STD	CERT	STD
	0	@ 50K	0.017 (0.085)		0.195	1.0	4.4	0.1	0.4		1	18	*		0.13	0.53
		@ 3011			(0.195)	(1.6)	(4.4)	(0.2)	(0.4	<u>)                                    </u>	(*)	(18)			(0.09)	(0.53)
	9 au	@ UL	0.017 (0.085)	•	0.280	1.0	6.4	0.1	0.6	;	1	27		*	0.13	0.80
	101504	@ OL			(0.280)	(1.6)	(6.4)	(0.2)	(0.6	i)	(*)	(27)			(0.09)	(0.80)
	@ 50°	F & 4K	*	*	•	*	*	•	*		*	•	*	•	*	•
				@ 4K (SULEV, ULEV, NMHC+NC) or 50K (Tier 1, TLEV) (compo					NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		iHC+NOx ni] [SC03]		[g/mi] C03]	
50			@ UL (Tier		CERT	STD	CERT	STD	CERT	ST	TD CE	RT ST	D CER	T STD	CERT	STD
CERT	(4.1)	1.5	SF	TP @ 4K	*	*	•		(0.2)	(0.	.6) (1	.0) (11.	8) (0.14	(0.44)	(0.8)	(4.0)
STD	(12.5)		SF	TP @ UL	(0.18)	(1.67)	•	*	*	•	* (1	.0) (19.	3) •	•	(0.8)	(6.4)
@	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2 EVAP				POR	ORATIVE FAMILY 3 EVAPORATIVE FAMILY 4				LY 4		
@ UL	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-0	RI	L ORV	R 3-D	2-D	RL	ORVR
CERT	0.6	0.5	0.00	(0.00)	0.6	0.5	0.00	(0.00)	*	*	*		*	*	*	*
	(0.6)	(0.5)	(0.00)	(0.09)	(0.6)	(0.5)	(0.00)	(0.09)								<del></del>
STD	2.5 (2.5)	3.0 (3.0)	0.05 (0.05)	(0.20)	2.5 (2.5)	3.0 (3.0)	0.05 (0.05)	(0.20)	*	*	*	*		*	•	*

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order. This Executive Order hereby supersedes Executive Order A-006-1245 dated July 14, 2004.

Executed at El Monte, California on this \_

day of September 2004.

Allen Lyons, Chief

Mobile Source Operations Division