

## DAIMLERCHRYSLER AG

EXECUTIVE ORDER A-003-0287 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODI		TEST GROUP			VEHICLE TYPE PC=passenger car; LDT=light-duty ( MDV=medium-duty vehicle; LVW=lo vehicle weight; ALVW=adjusted LV	aded vehicle	sion /:	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefled natural gas; LPG=liquefled petroleum gas)					
200		5MBXV03.2LBX			PC		NBin 8 ed as ARB LEV I ULE	,	100K / 100K	Flexible Fuel: Ethanol (E85) / Gasoline				
No.	FAMIL	EVAPORATIVE FAMILY (EVAF)		No	SPECIAL FEATUREMISSION CONTROL S	IRES & YSTEMS (ECS)	* = not applicable	OC/	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S					
1	5MBXF	R015	5LFZ	1	SFI, AIR, EGR, 2HO2	S(2), 2WUTWC, 2	<b>₩AF</b> S	S/MAFS=air-fuel ratio s	ensor/heated AFS EGRapyhauer					
2		•			·	•	gas AiR	gas recirculation AIR/PAIR=secondary air injection/puised AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger						
3	•			3		*	TBI							
4		•				*	diag	CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
EVAF No.		ECS ENGINE No. SIZE (L)			VEHICLE MAKES & MODELS	VEHICLES SUI STANDARDS	BJECT TO SFTP	ABBR	ABBREVIATIONS:					
1	1		2.6		Mercedes-Benz: C 240 (Sedan; Wagon)									
1	1	1 3.2			Mercedes-Benz: C 320 (Sedan; Wagon; Sportscoupe)									
*	* *													
*	*		*				*							

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]				@ RAF=* RAF = *	NMOG or									arbon mono		
CER	T ST	STD NMOG NMHC		NMHC	nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 da diurnal+hot-soak RL [g/mi]=running loss ORVR [g/galion dispensed]=on-board refueling vapor recovery g=gran mg=millilgram mi=mile K=1000 miles F=degrees Fahrenheit SFTP=supplemental federal test procedure										/ q≄gram	
0.05	054 0.049		CERT [g/mi]	CERT [g/mi]	[g/mi]	CO [g/mi]			NOx [g/mi]			[mg/mi]	PM [g/mi]		Hwy NOx [g/mi]	
· · · · · · · · · · · · · · · · · · ·	Artist Carpet			[8,111]		CERT	STD	CERT	ST	D	CERT	STD	CERT	STD	CERT	STD
	@	@ 50K 0.043 (0.028)		*	0.100 (0.100)	0.2 (0.3)	3.4 (3.4)	(0.04)	0.1 (0.1		0.4 (0.3)	15 (15)	•	*	0.002 (0.01)	0.19 (0.19)
		g UL	0.051 (0.034)	*	0.125 (0.125)	0.2 (0.4)	4.2 (4.2)	0.01 (0.05)	0.2		1 (1)	18 (18)	*	*	0.002	0.27 (0.27)
أشفعت	@ 50°F	& 4K	•	*	*	*	*	*	*		*	`•	*	*	*	*
CO [g/mi] SFTP 1 = @ @ 20°F & LEV) 50K SFTP 2 = @			V) or 50K (T	ier 1, TLEV)	NMHC+NC (compo	site)	CO [g/mi] (composite)		NMHC+No [g/mi] [US			CO [g/mi] [US06]		NMHC+NOx [g/mi] [SC03]		[g/mi] C03]
- 50	` .	SFTP 2 = @ UL (Tier		1, ILEV)	CERT	STD	CERT	STD	CERT	ST	D CE	RT STI	D CER	T STD	CERT	STD
CERT	(0.7)		s	FTP @ 4K	*	*	*	*	(0.04)	(0.1	(1	.3) (8.0	) (0.02	(0.20)	(0.03)	(2.7)
STD	(10.0)		s	FTP @ UL	(0.07)	(0.71)	*	•	*	•	(1.	.5) (11.	1) •	•	(0.2)	(3.7)
@ UL			TIVE FAM	AILY 1	EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3			MILY 3	EVAPORATIVE FAMILY 4			Y 4
	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RI	ORVI		2-D	RL	ORVR
CERT	0.7	2.2	0.004	0.02	*	*	*	•	•	*	<b>-</b>	*	+ + +	+	*	*
STD	2.0	2.5	0.05	0.20	*	*	•	*	*	*	<del>-</del>		<del></del>	<del></del>	<del> </del>	<del>                                     </del>

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

**BE IT FURTHER RESOLVED:** That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_\_\_ day of March 2004.

An Allen Lyons, Chief

Mobile Source Operations Division