

BAYERISCHE MOTOREN WERKE AG

EXECUTIVE ORDER A-008-0179
New Passenger Cars, Light-Duty Trucks
and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD		TEST GROUP				VEHICLE TYPE (PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=ioaded vehicle weight; ALVW=adjusted LVW)	EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV)			XHAUST & ORVR / EVAPORATIVE FUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)			
200		5BMXV03.0SMG				PC	ULE		100K / 100K (EVAF 1) 100K / 150K (EVAF 2)		Gasoline			
No.		NPORA IILY (E		N	0.	SPECIAL FEATURE EMISSION CONTROL SYS	ES & STEMS (ECS)	* = not appli						
1	5BMXR0136E46				1	2TWC, 2HAFS, 2H		MAPS/MAPS=air-fuel ratio s	ensor/heated AFS EGPmovhaume					
2	5BM	BMXR0090E60			2		+	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI						
3		•			3	i en	*	TBI= throttle body injection	n TC/SC=turbo /euros obornes					
4		•			4		+		CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series					
EVAF No.	- 1	CS No.	ENGIN SIZE (VEHICLE MAKES & MODELS S	VEHICLES SUBJ STANDARDS AR	ECT TO SFTI	D /	ABBREVIATIONS:				
1		1	2.5		BMW: 325i, 325Ci, 325Ci Convertible, 325i Sport Wagon									
1		1	3.0		BMW: 330i, 330Ci, 330Ci Convertible									
2		1	2.5		BMW 525i									
2		1	3.0			-	· · · · · · · · · · · · · · · · · · ·	BMW 53		~ · · · · · · · · · · · · · · · · · · ·				

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

AVE	NMOG FLEET N AVERAGE [g/mi]			NMOG @ RAF = * CH4 RAF = *								n-CH4 hydro				
CER	CERT STD		NMOG	NMHC	NMHC	mg=millg		- fArrulra	nning loss 1000 miles	UKV	r (g/ganoi	dispensed]	=on-board r	efueling vap plemental fe	or recover	/ d=dram
0.05	3	0.049	CERT [g/mi]	CERT [g/mi]	[g/mi]		[g/mi]		x [g/mi]		НСНО	[mg/mi]	PM [c	g/mi]		x [g/mi]
0.55 (0.040)						CERT	STD	CERT	ST)	CERT	STD	CERT	STD	CERT	STD
		@ 50K	0.012	*	0.040	0.7	1.7	0.05	0.2	:	0	8	*	•	0.01	0.3
		@ UL	0.013	•	0.055	0.8	2.1	0.1	0.3		0	11	*		0.01	0.4
	@ 50	°F & 4K	0.014	*	0.080	0.7	1.7	0.05	0.2		1	16			*	*
CO [@ 20	g/mi] °F&	SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)			NMHC+NOx [g/mi] (composite)		CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]			CO [g/mi] [US06]	NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
50	K	SFTP 2 = @ UL (T		1, TLEV)	CERT	STD	CERT	STD	CERT	ST					CERT	STD
CERT	1.3	SAC.		SFTP 1	*	*	*	•	0.12	0.1	4 2	4 8.0		0.20	0.8	2.7
STD	10.0	END	100	SFTP 2	*	*	*	*	•	*			*	*		*
@ UL		VAPORA	TIVE FAM	ILY 1	EVAPORATIVE FAMILY 2			EVAPORATIVE FAMILY 3				- F	VAPORAT	VE EAM	V 4	
<u>_</u>	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D						
CERT	1.0	1.9	0.02	0.07	0.23	0.31	0.02	0.12	*	*	, KL	ORVI	3-0	2-D	RL	ORVR
STD	2.0	2.5	0.05	0.20	0.50	0.65	0.05	0.20	•	*					*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _____ day of September 2004.

Allen Lyons, Chief

Mobile Source Operations Division